


3124

1513




CENTER

LABORATORY

TECHNICAL REPORT

NO. 12680

TECHNICAL  
REPORT WRITING  
**STYLE  
MANUAL**



OCT 1982  
FIRST REVISION - SEPT 1984

JAMES N. BOBLLENZ, WITH ALICE A. CALHOUN  
US ARMY TANK-AUTOMOTIVE COMMAND  
ATTN: AMSTA-TS

by WARREN, MI 48090

APPROVED FOR PUBLIC RELEASE:  
DISTRIBUTION UNLIMITED

Reproduced From  
Best Available Copy

U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090

20011025 141

REV. 01 AM-45782

## NOTICES

This report is not to be construed as an official Department of the Army position.

Mention of any trade names or manufacturers in this report shall not be construed as an official indorsement or approval of such products or companies by the US Government.

Destroy this report when it is no longer needed. Do not return it to the originator

## REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS None		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for Public Release: Distribution Unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) 12680			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION US Army Tank-Automotive Command		6b. OFFICE SYMBOL (If applicable) AMSTA-TSE	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) Warren, MI 48090			7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Tech Data Div		8b. OFFICE SYMBOL (If applicable) AMSTA-TS	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code) TACOM Warren, MI 48090 Bldg. 200A			10. SOURCE OF FUNDING NUMBERS		
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) TACOM Technical Report Writing Style Manual, First Revision					
12. PERSONAL AUTHOR(S) James N. Boblenz with Alice A. Calhoun					
13a. TYPE OF REPORT Interim		13b. TIME COVERED FROM Oct 82 TO Sep 84		14. DATE OF REPORT (Year, Month, Day) 84 Sep	
15. PAGE COUNT 94					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Technical report Proofreading symbols Writing style		
			Technical writing Grammar Report organization		
			Technical review Language usage Editing		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>This first revision of the style manual has been produced to assist authors, editors and production personnel in preparation of scientific and technical reports. Guidelines have been designed to provide specific instructions to different groups who write, edit, type and lay out copy for the US Army Print Plant or to conform to GPO printing requirements.</p> <p>This report consists of two main parts. Part I will be of interest to the author as it addresses standards of style, grammar, word usage, spelling aids, verbiage reduction tips and so on. Part II is of particular interest to production personnel as it describes and illustrates the mechanical aspects of report preparation in terms of format, treatment of tables and figures, pagination, numbering, cover format, organization, classification markings and proper referencing.</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL GLENN FINLEY			22b. TELEPHONE (Include Area Code) (313) 574-6499		22c. OFFICE SYMBOL AMSTA-TS



## PREFACE

The authors wish to acknowledge the contributions of several people whose help made this report possible: Mr. George Taylor, TACOM's Technical Editor, who provided valuable assistance through initial editing; Mr. Alexander Kovnat, Senior Mechanical Engineer in the Technical Editorial Office for his constructive and timely comments; and finally, Mrs. Hannalore Foster, Mrs. Roseann Romanski, and Mrs. Janet Grove, who did an excellent job in editing and programming the final version.

\*\*\*

This First Revision, dated September 1984, was written and edited by members of the R&D Center Editorial Staff: Mrs. Doris Hudgins, Mrs. Janet Grove, Mr. George Taylor, and Mrs. Christine Richard.

Suggestions to improve this report are welcome. Request for copies may be addressed to: Commander, US Army Tank-Automotive Command, Research and Development Center, ATTN: AMSTA-TSE, Warren, Michigan, 48090.

THIS PAGE LEFT BLANK INTENTIONALLY

## TABLE OF CONTENTS

Section	Page
1.0. INTRODUCTION . . . . .	11
2.0. REPORT ORGANIZATION, PURPOSE, AND FORMAT . . . . .	11
2.1. <u>Purpose of the Report</u> . . . . .	11
2.2. <u>Organization Requirements</u> . . . . .	12
2.2.1. Front Cover . . . . .	13
2.2.2. Notices . . . . .	13
2.2.3. Report Documentation Page, DD Form 1473 . . . . .	13
2.2.4. Summary . . . . .	13
2.2.5. Preface . . . . .	13
2.2.6. Table of Contents . . . . .	13
2.2.7. Lists of Illustrations and Tables. . . . .	13
2.2.8. Introduction . . . . .	14
2.2.9. Statement of Objectives . . . . .	14
2.2.10. Conclusions . . . . .	14
2.2.11. Recommendations . . . . .	15
2.2.12. Discussion (The Main Text) . . . . .	15
2.2.13. List of References . . . . .	15
2.2.14. Bibliography . . . . .	15
2.2.15. Appendices . . . . .	16
2.2.16. Glossary of Terms . . . . .	16
2.2.17. List of Abbreviations, Acronyms, and Symbols . . . . .	16
2.2.18. Alphabetical Index . . . . .	16
2.2.19. Distribution List . . . . .	16
2.3. <u>Format Requirements</u> . . . . .	17
2.3.1. General . . . . .	17
2.3.2. Page Size and Quality . . . . .	17
2.3.3. Indentation, Margins, Vertical Spacing, and Numbering Paragraphs . . . . .	17
2.3.4. The Front Cover . . . . .	19
2.3.5. "TABLE OF CONTENTS" Page . . . . .	21
2.3.6. "LIST OF ILLUSTRATIONS" Page . . . . .	23
2.3.7. "LIST OF TABLES" Page . . . . .	23
2.3.8. "LIST OF REFERENCES" Page . . . . .	23
2.3.9. "SELECTED BIBLIOGRAPHY" Page . . . . .	24
2.3.10. "DISTRIBUTION LIST" Page . . . . .	24
2.3.11. Tables . . . . .	24
2.3.12. Figures . . . . .	26
2.3.13. Headings . . . . .	27
2.3.14. Binding . . . . .	29
2.3.15. Numbers in the Text . . . . .	29
2.3.16. Pagination . . . . .	30
3.0. PUNCTUATION AND CAPITALIZATION . . . . .	31
3.1. <u>General</u> . . . . .	31
3.2. <u>Punctuation</u> . . . . .	32
3.2.1. Period . . . . .	32

# TABLE OF CONTENTS (Continued)

Section	Page
3.2.2. Comma . . . . .	32
3.2.3. Colon . . . . .	33
3.2.4. Bullets . . . . .	33
3.2.5. Parentheses and Brackets . . . . .	34
3.2.6. Italics . . . . .	34
3.2.7. Hyphen . . . . .	34
3.2.8. Degree Sign. . . . .	34
3.2.9 Odds and Ends. . . . .	35
3.3. <u>Capitalization</u> . . . . .	35
3.3.1. General. . . . .	35
3.3.2. Capitalization of Headings . . . . .	35
3.3.3. Capitalization of Proper Names . . . . .	35
3.3.4. Capitalization of Abbreviations . . . . .	35
4.0. ABBREVIATING AND COMPOUNDING . . . . .	35
4.1. <u>Abbreviating</u> . . . . .	35
4.2. <u>Compounding</u> . . . . .	37
4.2.1. General Rules . . . . .	37
4.2.2. Unit Modifiers . . . . .	39
4.2.3. Technical Terms . . . . .	40
4.2.4. Numeric Compounds . . . . .	40
4.2.5. Fractional Numeric Compounds . . . . .	40
4.2.6. Capital Letter Words . . . . .	41
4.2.7. Improvised Words . . . . .	41
5.0. SPELLING . . . . .	41
5.1. <u>Spelling Called for by Government Printing Office Style Manual</u> .	41
5.2. <u>Words Easily Misspelled</u> . . . . .	42
5.2.1. Double Consonants. . . . .	42
5.2.2. Endings "cede," "ceed," "sede." . . . .	43
6.0. READABILITY . . . . .	43
6.1. Standards (DARCOM-P 310-10 and DA Cir 310-9) . . . . .	43
6.2. <u>Word Choice</u> . . . . .	43
6.2.1. Using Simple Language . . . . .	43
6.2.2. Avoiding Word Confusion Errors . . . . .	44
6.2.3. Overworked Words and Phrases to be Avoided in Writing . . . . .	45
6.3. <u>Sentence Structure and Grammar</u> . . . . .	45
6.3.1. Tense . . . . .	46
6.3.2. Voice . . . . .	46
6.3.3. Parallel Elements . . . . .	47
6.3.4. Emphasis . . . . .	47
6.3.5. Wordiness . . . . .	47
6.3.6. The Complexity of <u>a</u> and <u>an</u> . . . . .	47
7.0 DOCUMENTATION . . . . .	48
7.1 <u>Using Footnotes</u> . . . . .	48
7.1.1. In the Text . . . . .	48

## TABLE OF CONTENTS (Continued)

Section	Page
7.1.2. In Tables . . . . .	48
7.2. <u>Preparing the "List of References"</u> . . . . .	49
7.3. <u>Including a Bibliography</u> . . . . .	49
7.4. <u>Including an Index</u> . . . . .	49
7.5. <u>Security Marking Documentation</u> . . . . .	49
8.0. EDITING . . . . .	50
8.1. <u>Relationship between Editor and Writer</u> . . . . .	51
8.2. <u>Relationship between Editor and Typist</u> . . . . .	52
8.3. <u>Proofreading Symbols</u> . . . . .	52
LIST OF REFERENCES . . . . .	55
SELECTED BIBLIOGRAPHY . . . . .	57
APPENDIX A. MODEL REPORT . . . . .	A-1
APPENDIX B. GUIDELINES FOR WRITING TECHNICAL DEFINITIONS . . . . .	B-1
APPENDIX C. GUIDELINES FOR WRITING TECHNICAL DESCRIPTIONS OF OBJECTS . . . . .	C-1
DISTRIBUTION LIST . . . . .	Dist-1

THIS PAGE LEFT BLANK INTENTIONALLY

## LIST OF ILLUSTRATIONS

Figure	Title	Page
2-1.	Margins and Spacings. . . . .	18
2-2.	Blank Front Cover . . . . .	20
2-3.	Sample Cover for a Contractor-Prepared Report . . . . .	22
2-4.	Sample Cover for Contractor-Authored Report with Contractor's Report Number Assigned. . . . .	22
2-5.	Sample Cover for Combined Contractor- and TACOM-Prepared Report . .	22
2-6.	Sample Cover for an In-House Prepared Report. . . . .	22

THIS PAGE LEFT BLANK INTENTIONALLY

## 1.0. INTRODUCTION

This manual, prepared by the Technical Editorial Office as a Style Guide for US Army Tank-Automotive Command (TACOM) Research and Development technical report writers, is designed to make the operation of the Technical Editorial Office more efficient, thereby increasing its productivity. One of the jobs of the office is to make sure that technical reports clearly convey and effectively document the objectives, conclusions, recommendations, materials, and methodology of engineering projects. Currently, a number of government documents offer advice on the preparation of technical reports, yet each varies in some way from the others. Believing that standardizing format would simplify the reporting process, the office published a style manual in May of 1981 and revised that edition in June of the same year. Nevertheless, reports have continued to reveal variations in format and mechanics. As a result, the office still spends as much time standardizing such variations as it does in clarifying the logical statement of ideas. To minimize the occurrence of such variations, the office has prepared a style manual which offers additional guidance for technical report writers on:

- overall organization, purpose, and format;
- punctuation and capitalization;
- abbreviating and compounding;
- spelling and word choice; and
- documentation.

## 2.0. REPORT PURPOSE, ORGANIZATION, AND FORMAT

### 2.1. Purpose of the Report

In composing a technical report, the engineer must keep in mind that his major goal is to provide managerial personnel with the amount and type of information needed to effectively evaluate his project. To do this, the engineer must understand the characteristics of the manager.

First, although most managers are very interested in all engineering projects and would like to spend a good deal of time thoroughly studying the details of each report, they are so overburdened by administrative duties that they cannot possibly do this. The typical manager will carefully read the introduction, the statement of objectives, the conclusions, and the recommendations, but will usually only skim the rest of the report. Thus, the reporting engineer, when writing a report, should make sure that all of his major points are clearly and concisely spelled out in the opening sections.

Secondly, the engineer must be aware of the educational level and experience of his managerial audience. He can, of course, expect his readers to

be highly literate and to have a substantial knowledge of engineering methods and materials, especially those directly related to TACOM's mission. However, he cannot expect managers to have highly specialized knowledge of specific engineering fields or of complex mathematics. He will, then, want to make sure that new terminology, complicated procedures, or innovative techniques are clearly defined.

Thirdly, the engineer must be aware of the special goal orientation of managers. While they are certainly interested in immediate or short-range effects of separate R&D projects, their primary orientation is toward long-range effects and their concern is with the effective integration of all TACOM projects within their divisions. Therefore, in providing background, in stating goals and results, and in offering suggestions for improvements, the engineer must show what his particular project contributes to the overall mission of the US Army Tank-Automotive Command. Finally, although the average manager will not be able to study the details as thoroughly as he would like, the writer must be careful to accurately and thoroughly document the materials and methods of his project. On occasion, the manager may be asked to justify his recommendations. He should be able to find all the details he needs in the main text of the report.

In sum, the engineer must provide the managers with the quantity and quality of information that they need to make decisions regarding future projects. Understanding the overall purpose of the technical report, the engineer must then begin to focus on the specific purpose of each section. (The sections that are not discussed in detail here need no explanation.)

## 2.2. Organization Requirements

Although all reports do not necessarily contain all of the following elements, those that are used will appear in the following order with the abstract appearing only on the Report Documentation Page, DD Form 1473.

### Front Matter

- Front Cover (Required)
- Notices
- Report Documentation Page, DD Form 1473 (Required)
- Summary
- Preface
- Table of Contents
- List of Illustrations
- List of Tables

### Body of the Report

- Introduction
- Objectives
- Conclusions
- Recommendations
- Discussion (Main Text)

#### Reference Material

- List of References
- Bibliography
- Appendices
- Glossary of Terms
- List of Abbreviations, Acronyms, and Symbols
- Alphabetical Index (Recommended for Long Reports)
- Distribution List
- Back Cover

2.2.1. Front Cover. The cover page requires little effort on the author's part. The Technical Editorial Office has standard "prepared" front covers that are to be used on all TACOM Technical Reports. Instructions for cover preparation are at par. 2.3.4.

2.2.2. Notices. Notices concerning Department of Army position on the report, endorsement of products and companies mentioned in the report, and uses of the report when it is no longer needed, are to be placed on the inside of the front cover. (See inside front cover of this report and par. 2.3.16.2.)

2.2.3. Report Documentation Page, DD Form 1473. The Report Documentation Page serves as the title page in DOD reports and is page one (the back is page two) in every report. This form, including detailed instructions for its completion, should be picked up by the TACOM project engineer from the Technical Editorial Office and completed before the report is submitted for editorial review. Although the instructions are quite thorough, one additional point should be noted. Guidance in choosing the "Subject Terms" asked for in Block 18 can be found in a draft of a Manufacturing Methods and Technology (MMT) guide on file in the Technical Editorial Office.

2.2.4. Summary. A summary may be included to provide a digest of the report, to explain the reason for the initiation of the work, and to outline principal conclusions and recommendations. A summary may be used to give more information on the content of the report than can be presented in the abstract entered on the Report Documentation Page, DD Form 1473.

2.2.5. Preface. If a preface is used, it may show the relationship of the work reported on in conjunction with associated efforts, give credit for the use of copyrighted material, or acknowledge significant assistance received.

2.2.6. Table of Contents. The purpose of the Table of Contents is to provide a quick overview of and ready access to report sections. As such, the Table of Contents should list the numbered report headings of each section and the page number on which that section begins. Format guidelines are provided in par. 2.3.5.

2.2.7. Lists of Illustrations and Tables. Like the Table of Contents, these lists provide quick overviews of and guides to figures and tables. If each list is shorter than one half page, they may be typed on the same page. Format guidelines are found in pars. 2.3.6. and 2.3.7.

2.2.8. Introduction. The Introduction of a technical report provides management with the background, scope, and purpose of a particular engineering project. Additionally, where possible, it relates the specific objectives of the project to overall divisional objectives or to the TACOM mission. Usually written in past tense, it can, nevertheless, be written either as a single paragraph or as a series of numbered paragraphs; the decision should be based on the complexity of the material. In writing a single paragraph introduction, the technical report writer may wish to use the introductory paragraph of the sample report (see APPENDIX A) as a sample. Examples of other introductions are on file in the Technical Editorial Office. In studying these introductions, the writer should note that the first sentence includes:

- the name of the contractor (if the project is not in-house);
- the Department of Army contract number; and
- a summary of the project purpose.

The first two items given above are omitted from the introduction and included in the preface of a long report, along with details regarding contributions of individual engineers or private subcontractors. Additional sentences in the introduction provide--in as few words as possible--information on (1) the problem(s) the project has sought to solve, (2) the methods and materials used to alleviate each problem, and (3) the results of these efforts. In providing such information, the engineer may wish to include a few brief (no more than one-sentence) definitions of terminology concerning the object of experimentation (such as a track system) or methods used (such as blow-molding or laser treatment). Instructions on writing definitions are given in APPENDIX B. The engineer may also wish to offer concise analysis of the advantages of the current process or product.

2.2.9. Statement of Objectives. The purpose of the "objectives" paragraph is to describe the results that were intended (but not necessarily achieved) by those involved in the effort which the report addresses. In this section, the author delineates the hoped-for accomplishments, even if the actual outcome of the work fell short of these expectations. The manner in which the engineer states these objectives is dependent upon their complexity. If, for example, he can state the objective(s) in a sentence of 25 words or fewer, he may do so. (See "Objective," p. A-13.) On the other hand, in a case involving several complex objectives of this project where "the following:" is used, list them as "bulleted" parallel independent clauses. The words "the following" are not needed when the bulleted items are dependent clauses. Such clauses should be parallel in structure. (See par. 6.3.3.)

2.2.10. Conclusions. Conclusions summarize the success achieved or, in any instance, the knowledge gained as a result of the work described in the report. If at all possible, the statement of the conclusions should parallel the content of the objectives.

2.2.11. Recommendations. Extremely important information, the recommendations allow the engineer to convey to managerial personnel the steps that can be taken to insure future success. Recommendations could also include advice on follow-on research projects related to divisional objectives or overall Command mission.

2.2.12. Discussion (The Main Text). As the bulk of the report, the section titled "Discussion" is of great importance in substantiating the assertions made in the Introduction, Objective(s), Conclusions, and Recommendations. The engineer should, therefore, spare no effort in providing a detailed record of materials, tools, and methods involved in his project. He may organize and develop the content of the body in any manner he wishes. General headings he may consider:

- Materials,
- Design,
- Fabrication,
- Testing,
- Theoretical Formulation, and
- Packaging.

Not only should he provide a narrative summary of the various stages of research and development, but he should also provide as many tables and figures as he needs to clarify and illustrate points made in the text. It is important for him to note that photographs or drawings are meant to be visual counterparts of verbal descriptions in the text; they are not substitutes for text.

The same principle applies to graphs and tables. All the major points that these figures, graphs and tables illustrate should be part of a detailed discussion in the text. In addition, major types of information presented in a table or graph and viewpoints to be discerned should be explicitly stated at the point in the text where the table is first mentioned. Finally, each table and figure should be placed on a separate page as close as possible to the point in the main text where it is first mentioned. (See pars. 2.3.11. and 2.3.12. for further guidance on tables and figures.)

2.2.13. List of References. When it is necessary to cite references, identify the source to aid future readers. The references should be listed in the same numeric order as cited in the text, and in a reference list, which follows the body of the report. (See par. 7.2.)

2.2.14. Bibliography. The bibliography, if included, is a selected list of information sources which were consulted but not quoted in the text. (See par. 7.3.)

2.2.15. Appendices. Appendices include material that is parenthetical or supplementary to the main text. In other words, material may be placed in an appendix if its inclusion in a text would disrupt the normal flow of ideas due to the amount of detail required or because it is only peripherally related to the discussion. Occasionally, related reports or studies--parts of which have been cited in the text--are included in appendices. John M. Lannon in Technical Writing gives these possible items to be included as appendices:

- details of an experiment;
- statistics;
- maps;
- complex formulas;
- long quotes (one or more pages);
- texts of laws, regulations, etc.;
- related correspondence (letters of inquiry, etc.);
- interview questions and responses;
- sample questionnaires and tabulated responses; and
- sample tests and tabulated results.

2.2.16. Glossary of Terms. Unusual terms should be described, either in the text or as parenthetical notes, when first used in the body of the report. When many such terms are used, list them alphabetically with appropriate definitions in a glossary.

2.2.17. List of Abbreviations, Acronyms, and Symbols. Define abbreviations, acronyms, and symbols when first used in the report. If they are numerous, list them in alphabetical order and with appropriate definitions on a separate page at the end of the report.

2.2.18. Alphabetical Index. For long reports, an alphabetical index is recommended.

2.2.19. Distribution List. A distribution list must be included as the last page(s) of each technical report. As a minimum, the following addresses must be included on the list.

- (1) Commander  
Defense Technical Information Center  
Bldg. 5, Cameron Station  
ATTN: DDAC  
Alexandria, Virginia 22314

- (2) Manager  
Defense Logistics Studies  
Information Exchange  
ATTN: DRXMC-D  
Fort Lee, VA 23801
- (3) Commander  
US Army Tank-Automotive Command  
ATTN: AMSTA-TSL (Technical Library)  
Warren, MI 48090

If the report has limited distribution, two copies should be sent to the first two addresses; if the distribution is unlimited, 12 copies are to be mailed to the first address, with two copies going to the second address. Regardless of distribution limitations, two copies are to be sent to the third address. An extended listing of optional distribution points and their addresses is on file at the Technical Editorial Office and may be referred to at any time.

### 2.3. Format Requirements

2.3.1. General. The Technical Editorial Office has adopted a standard format so that office publications will be of a uniform quality. These formal requirements are based on the criteria explained in AR 70-31, in MIL-STD-847B, and in the US Government Printing Office (GPO) Style Manual. Departures from these guidelines have been made to make the reporting process more efficient.

2.3.2. Page Size and Quality. All report pages, including illustrations and tables, should be typed on 8½- by 11-inch white paper. Because of expenses incurred in printing, foldout pages should be avoided, if at all possible.

2.3.3. Indentation, Margins, Vertical Spacing, and Numbering Paragraphs.

2.3.3.1. Indentation. Block style should be used throughout the majority of the report; with the exception of "bulleted" items (see par. 3.2.4.) and general explanatory material, all headings in the body and lines of copy should be flush left and numbered.

2.3.3.2. Margins. (Figure 2-1). The following guidelines on margins should be adhered to. The margin at the top of the page should be no narrower than one inch. The margin at the bottom of the page should be no narrower than one inch. (Please note that the page number is considered as part of the copy, that there is a ½-inch space between the text and the page number, and there must be a full one-inch margin below the number.) Gutter margins (the inner margins between facing pages) should be at least 1¼ inches wide, and outer margins should be at least one inch wide. If copy cannot be printed on both sides of the page, left margins should be at least 1¼ inches wide, and right margins should be at least one inch wide.

2.3.3.3. Vertical spacing. Vertical spacing involves spacing within a single section of text and spacing between sections. As a general rule, the

1 inch or 6 lines

First line of copy

← Margins for pica (10 pitch) = 13 and 75 →

← Margins for elite (12 pitch) = 15 and 90 →

1¼ inch →  
or  
13 spaces  
(pica)  
or  
15 spaces  
(elite)

51 lines of copy

1 inch  
or  
10 spaces  
(pica)  
or  
12 spaces  
(elite)

Bottom line of copy

1½ inch  
or  
9 lines

Page number line

1 inch or 6 lines

Figure 2-1. Margins and Spacings

text of technical reports is to be single-spaced. One exception is seen with "bulleted" items (see par. 3.2.4.); there is usually a blank line between the text and the first bulleted point and a blank line separating each point. Another exception involves spacing between headings in the text. The first major heading in the body is preceded by a one-inch margin and is followed by two blank lines. All other major headings in the main text are both preceded and followed by one blank line. Secondary headings are separated from other secondary headings by one blank line. All lower level headings are separated from one another by one blank line. A third exception concerns the placement of centered headings on the cover sheets of appendices and addenda. The word "APPENDIX" or "ADDENDUM" is centered horizontally and vertically. Make sure that two blank lines separate the section title from the heading. If the title runs more than one line, it is double-spaced. Finally, the writer must be aware that each of the following sections always begins on a right-hand page: front matter--all sections (except when lists of tables and illustrations are short enough to appear on the same page), body of the report--the introduction; and reference material--all items.


2.3.3.4. Numbering paragraphs. As a general rule, all paragraphs in technical reports are headed and numbered. This procedure provides abbreviated reference terms for entire sections of text. Thus, material that is frequently referenced--a government specification, for example--is readily accessible. However, a report occasionally includes background, or introductory material that is of such a general nature that it need not be presented as a series of numbered paragraphs. Usually such material is preceded by appropriate heading numbers and the heading "General." (See par. 2.3.13.) By and large, paragraphs in such sections should be no longer than 150 words.

2.3.4. The Front Cover. The general format for all TACOM technical reports is illustrated in Figure 2-2. Such blank "working covers" may be picked up from the Technical Editorial Office. The project engineer then fills in the following items.

2.3.4.1. Defense Technical Information Center (DTIC) control number. The rectangle in the upper right-hand corner should be left blank for the accession number assigned at the Defense Technical Information Center in Alexandria, Virginia.

2.3.4.2. The report number. Before it is edited, each report is assigned a report number by the Technical Library Services Branch, AMSTA-TSL, and recorded on a log in the Technical Editorial Office. When the report is sent in final form to the printing office, this report number is placed on the blank line following the heading which reads "R and D Center Laboratory Technical Report."

2.3.4.3. The report title. The title is separated from the report number by one blank line. All letters in a title are capitalized, and the title is centered. If the title runs more than one line, the second line should be centered under the first line as seen in Figure 2-3. In choosing words for the title, the writer should be careful to use the same technical terminology that is used by the Army in its project contract title. However, whenever



CENTER

LABORATORY

TECHNICAL REPORT

NO. \_\_\_\_\_



by \_\_\_\_\_

**U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090**

Figure 2-2. Sample Blank Front Cover

possible, the engineer is advised to use widely known terms in the title so that the report can be readily accessible through systems which index by key terms. Also, the report title should always be unclassified, if possible, even in a classified report.

2.3.4.4. The contract number. If used, the Department of Army contract number is separated from the title by one blank line.

2.3.4.5. The report date. The date (month and year) that the technical report was completed is centered beneath the contract number. This date should be the same as the date in Block 14 on the Report Documentation Page, DD Form 1473. Block 13b of DD Form 1473 gives the dates that the project itself was begun and completed. (All other dates should be written in government style, i.e., 5 Jan 84.)

2.3.4.6. Author credit line. Author credits are printed in the space above the "by" line. Figures 2-3 through 2-6 illustrate the credit lines for the four types of reports submitted to the Technical Editorial Office: a sample cover for contractor-prepared report (Figure 2-3); a sample cover for contractor-authored report with contractor's report number assigned, (Figure 2-4); a sample cover for combined contractor- and TACOM-prepared report, (Figure 2-5); and a sample cover for an in-house prepared report, (Figure 2-6).

2.3.4.7. Distribution statement. Limitations concerning distribution are indicated two blank lines below and to the left margin (see Figure 2-6). An extended discussion of distribution statement may be found in DOD Directive 5200.20.

2.3.5. "TABLE OF CONTENTS" Page (see Tables of Contents on pp. 5 through 7 and p. A-7).

2.3.5.1. General. In formatting the Table of Contents page, the writer must pay close attention to placement, numbering, and capitalization of headings and to placement of page numbers.

2.3.5.2. Placement of titles. The writer should note that the first printed line on the page begins one inch from the top and contains the centered title in all capitals. The title is followed by two blank lines. On the third line below the title, flush with the left margin, should appear the word "Section," of which only the first letter is capitalized. On the same line, flush with the right margin, is the word "Page;" here, as well, only the first letter is capitalized.

2.3.5.3. Choice of headings. Leaving one blank line after the "Section/Page" line, the writer then begins a flush-left listing of report headings. Since it is not necessary to include front matter in the table, the list begins with body headings. They are listed with the same numbers and in the same form as in the text. (See par. 2.3.13.) With a short report, only major headings need to be listed. In longer reports, tertiary headings may be included. Fourth-level headings are not included. Only

**R and CENTER  
LABORATORY  
TECHNICAL REPORT**

NO. 12624

ATEPS CORE ELEMENT  
MINIATURIZATION

CONTRACT NUMBER DAAK30-80-C-0070

If the project is under the requirements of AR 5-14, the following statements are required.

This contract was noncompetitively awarded  
OR  
This contract was competitively awarded based on (technical or cost) factors.

John Beard  
Chrysler Corporation  
Huntsville Electronics Division  
102 Wynn Dr  
Huntsville, AL 35805

by

Test and Evaluation Document. Distribution Limited to US Government agencies only. Other requests for this document must be referred to USATACOM, ATTN: DRSTA-TS

**U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090**

Figure 2-3. Sample Cover for Contractor-Prepared Report.

**R and CENTER  
LABORATORY  
TECHNICAL REPORT**

NO. 12666

LASER HEAT TREATMENT OF TRACK  
COMPONENTS IN COMBAT VEHICLES  
(PHASE I)

CONTRACT NUMBER DAAK30-81-C-0136

If the project is under the requirements of AR 5-14, the following statements are required.

This contract was noncompetitively awarded.  
OR  
This contract was competitively awarded based on (technical or cost) factors.

D.S. Gnanamuthu & R.J. Moore  
Rockwell International Science Center  
Thousand Oaks, CA 91360  
Rockwell Report No. SC5248 12 F8

by

Proprietary Information Document! Distribution Limited to US Government agencies only. Other requests for this document must be referred to USATACOM, ATTN: DRSTA-TS

**U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090**

Figure 2-4. Sample Cover for Contractor-Authored Report with Contractor's Report Number Assigned.

**R and CENTER  
LABORATORY  
TECHNICAL REPORT**

NO. 12612

INFRARED RADIATION IN A NATURALLY  
OBSCURD ATMOSPHERE, PROPAGATION OF

CONTRACT NUMBER DAAK30-82-G-0002

If the project is under the requirements of AR 5-14, the following statements are required.

This contract was noncompetitively awarded.  
OR  
This contract was competitively awarded based on (technical or cost) factors.

L.W. Winchester, Jr.  
G.G. Gimmedstad, & S.H. Lea  
Kawco Research Center  
Michigan Technological University  
Houghton, MI  
and  
David E. Wilburn  
US Army Tank-Automotive Command  
ATTN: DRSTA-TSC  
Warren, MI 48090

by

Approved for Public Release:  
Distribution Unlimited.

**U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090**

Figure 2-5. Sample Cover for Combined Contractor-and TACOM-Prepared Report.

**R and CENTER  
LABORATORY  
TECHNICAL REPORT**

NO. 12574

FAILURE ANALYSIS STUDIES  
OF T-142 TRACK PADS

JUNE 1982

Jacob Pott & Peter G. Sakelns  
US Army Tank-Automotive Command  
ATTN: DRSTA-RCKT  
Warren, MI 48090

by

Approved for Public Release:  
Distribution Unlimited

**U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090**

Figure 2-6. Sample Cover for an In-House Prepared Report.

rarely will headings below this level be incorporated in the table. The table also cites the list of references, appendices with corresponding titles (e.g., APPENDIX A: SAMPLE REPORT), distribution list, and other back matter.

2.3.5.4. Vertical spacing of headings. Major headings are separated from other headings by one blank line. Secondary and tertiary headings follow one another directly.

2.3.5.5. Horizontal spacing of table items. With numbered headings, the space between the period after the last number and the words of the headings depends on the levels of headings included in the table. When only major and secondary headings are included, two spaces separate the number and the first word of each heading. When three levels are included, four spaces separate the numbers and first words of major and secondary headings and two spaces separate the numbers and first words of tertiary headings. In all cases, the first letter of each heading is vertically aligned. The last word of each heading is separated from the page number on which the section begins by spaced periods. These periods stop at the space preceding the space under the "P" in the word "Page." (See the Tables of Contents of this manual.)

2.3.5.6. Page numbers. Page numbers are listed flush right.

2.3.6. "LIST OF ILLUSTRATIONS" Page. The title for this page is centered one inch from the top and is typed in all capitals. On the third line below the title, flush with the left margin is the capitalized word "Figure." In the center of the line is the capitalized word "Title." On the same line, flush right, is the capitalized word "Page." Beginning on the second line below the word "Figure" are the figure numbers. Each figure is given two numbers which are separated by a hyphen and followed by a period: the first is the number of the major section in which it occurs. The second is based on the order on the figure within the section and is recorded in Arabic numerals, (e.g., the fourth figure in the second section would be numbered 2-4.). The figure title is separated from the number by at least two blank spaces. (All titles should, however, be aligned.) Titles are separated from their correspondent flush-right page numbers by spaced periods. One blank line separates each entry.

2.3.7. "LIST OF TABLES" Page. If the Lists of Illustrations and Tables are each less than one page, they may be placed on the same page. With the obvious difference of title, the format of the "LIST OF TABLES" page is identical to that of the "LIST OF ILLUSTRATIONS" page with one exception: the capitalized word "Table" is written over the listing of table numbers.

2.3.8. "LIST OF REFERENCES" Page. The title of this page appears in all capitals one inch below the top of the page. The list of references begins on the third line below the title. Referenced items are preceded by Arabic numerals in ascending sequence. These numerals are raised one half space and are separated from the publication information by two blank spaces. Each citation is single-spaced, and one blank space is left between citations. The page number continues the consecutive pagination of the body. (See par. 7.2. for specific information on documentation forms of individual items.)

2.3.9. "SELECTED BIBLIOGRAPHY" Page. Like the list of references page, the title of this page appears in all capitals one inch below the top of the page. The list of references begins on the third line below the title. Referenced items are listed alphabetically by the author's last name. When the author's name is not available, the title of the work is listed first (or, as in the case of an Army regulation or military standards or specifications, the acronym and number are first), in the same alphabetical sequence. Each entry is single-spaced. The second and all subsequent lines of each entry are indented five spaces. One blank space is left open between entries. The page number continues the consecutive pagination of the body. (See par. 7.3. for specific information.)

2.3.10. "DISTRIBUTION LIST" Page. The format for the distribution list page is similar to that of the table of contents and lists of tables and figures. The centered heading--"DISTRIBUTION LIST"--is typed in all caps one inch from the top of the page. On the third line below the title, flush with the right margin, is printed the word "Copies," of which the first letter is capitalized. On the fifth line below the title, flush with the left margin, begins a listing of the addresses to which the report is to be sent. The addresses themselves are single-spaced while there is a blank space between each complete address. Directly across from the first line of each address, flush with the right margin, is printed the number of copies to be mailed to that address. The page numbers of the list begin a new series of ascending Arabic Numerals preceded by the distribution, e.g., page one has centered at the bottom Dist-1, page two has Dist-2, etc.

#### 2.3.11. Tables.

2.3.11.1. General. Each table included in the body text of a report should be adequately introduced. Such references should summarize the contents of the table, clarify the relationship among the table elements, and explain the perspectives to be discerned. A table is meant to clarify highly detailed text information through its format. However, a table should always be accompanied by thorough text analysis.

2.3.11.2. Placement of tables in the text. For the most part, each table is to be placed on a separate page of text as close to the point at which it is first mentioned as is possible. In other words, unless the table is extremely short, it is not to be run in with the narrative. Occasionally, two short tables referenced on the same page of text may be put on a single page immediately following the text reference. (See p. A-18.) However, in no case are tables referenced in the text to be grouped together as an appendix. Additionally, tables should be restricted to a single page if possible. If the table material cannot fit on a single page, two solutions are acceptable. Preferably, the table copy will be photographically reduced so that it will fit on a single page. If the table must run more than one page, the table heading followed by the capitalized word "Continued" in parenthesis, the table title, and the table column headings must be repeated at the top of each additional page of the table.

2.3.11.3. Placement on page. Unless it is not possible to do so and maintain readability, place tables so that they may be viewed without turning the

page sideways. If this is not possible, place each table sideways so that it can be seen by rotating the page clockwise.

2.3.11.4. Table heading and title. The table heading and title begin at the left margin on a line that is one inch from the top of the page. The word "Table," the first letter of the first word in the title, and the first letter of all other important words in the title are capitalized. All letters in the word "Table" are followed by a two-part Arabic numeral separated by a hyphen, the first part being the number of the section in which the table appears and the second part, a number indicating the order of the table within the section. For example, the second table in section five of a report would have this heading--Table 5-2. The heading is followed by a period and is separated from the table title by two blank spaces. The title should be completed on one line if at all possible. If additional lines are necessary, they should be flush with the first letter of the first word in the title.

2.3.11.5. Related tables. Tables that present similar information should use similar formats.

2.3.11.6. Use of unbroken vertical and horizontal lines. Unbroken vertical lines should not be used either as margin-borders or as dividing lines between table columns. Unbroken horizontal lines, however, may be used in tables. Double horizontal lines are frequently used to enclose the actual table material; that is, they are used: (1) between the table heading/title and the column titles (or top-heads), and (2) between the table data columns and the footnotes (see p. A-18). A single unbroken horizontal line separates column titles and the data columns themselves.

2.3.11.7. Column top-heads. Column top-heads are separated from the double horizontal lines above them by one blank line and from the single horizontal line below them by one blank line. Unless it is impossible, each top-head is stated as a single word, of which only the first letter is capitalized. When the top-head is composed of several words, only the important words are capitalized. Further, when both single-line and multiline top-heads occur in the same table, the single-line top-heads are aligned with the second lines of the multiline heads.

2.3.11.8. Column/heading alignment. If the top heading is wider than the column, the column material is centered beneath it; if the column material is wider, the top-heading is centered above it.

2.3.11.9. Column data alignment. In all cases where decimals appear in column data, the decimals are aligned. Numbers without decimals are right-justified so the last digits of all numbers align vertically.

2.3.11.10. Table footnotes. Table footnotes are placed below the double horizontal line following the table data. To avoid confusion with table numerals (especially in table material involving exponents), the GPO Style Manual recommends the use of asterisks, daggers, etc. or superior letters. The order of symbols should be as follows: asterisk (\*), dagger (†), double

dagger (†), section mark (§), and parallel (/).<sup>2</sup> If such symbols are difficult to reproduce, superior letters may be used. The symbol or letter is flush left, and the footnote material follows it directly.

2.3.11.11. Pagination. Table page numbers continue the sequential pagination of the text. The page number is placed on a line that is one inch from the bottom of the page.

#### 2.3.12. Figures.

2.3.12.1. General. Each figure (or illustration) should be thoroughly explained in the main text. If the figure is a graph or chart, the reader should be given a thorough analysis of the relationship among the elements shown in the figure. Never should one rely on so vague a statement as "Results of these tests are shown in Figure 3-4." If the figure is a photograph or line drawing, the writer should provide equivalent verbal description in the text. APPENDIX C provides instructions in writing technical descriptions.

2.3.12.2. Placement of figures in the text. Each figure is to be placed on a separate page of text as close to the point at which it is first mentioned as is possible. In no case are figures referenced in the text to be grouped as an appendix. It is, however, acceptable to give two views of a single object (from different angles, from different distances, etc.) on the same page. When such is the case, they are labeled (a) and (b), and each letter is followed by a brief title explaining the view. All important words are capitalized in these titles.

2.3.12.3. Placement of figures on the page. Like tables (see par. 2.3.11.3.), most figures should be placed so that they can be read without turning the page sideways. If the figure must be placed sideways, it should be placed so that it is read by turning the page clockwise.

2.3.12.4. Figure heading and title. The figure heading and title begin at the left margin at least two lines below the figure. The first letter of the first word in the title, and the first letter of all other important words in the title are capitalized. The word "Figure" is followed by a two-part Arabic numeral separated by a hyphen, the first part being the number of the section in which the figure appears and the second part a number indicating the order of the table within the section. For example, the third figure in section one would be designated as Figure 1-3. This heading is followed by a period and is separated from the figure title by two spaces. The title should be completed on one line if possible. If additional lines are required, they should be flush with the first letter of the first word in the title.

2.3.12.5. Related figures. Figures that present similar information should use similar formats.

2.3.12.6. Legends. With the exception of self-explanatory photographs or drawings, many illustrations are accompanied by descriptive legends. Here

the term "Legend" differs slightly from the way it is used in MIL-STD-847B. That document uses the word "Legend" in the sense that the word "Title" has been used here. In this document, "Legend" refers to a brief list explaining the various symbols or colors used on a chart or graph. The explanatory material can be placed in a blank space on the figure itself or it can be placed in a space below the actual figure and above the figure title. But legends should never be placed within blank areas on a drawing; they are to be set off to the side or below.

2.3.12.7. Callouts. So far as practical, place callouts horizontally, unboxed, and near the item called out. Make callouts consistent in size and typeface throughout a report. Use lettering of at least 8-point or larger in a final reproduced size.

2.3.12.8. Foldouts. Foldouts are expensive to reproduce and should be avoided, if possible.

2.3.12.9. Use of photographs, diagrams, and drawings. Photographs, diagrams, and drawings are extremely important in technical reports in that they serve as visual equivalents of verbal descriptions. However, each has its own special merit, according to Theodore A. Sherman and Simon S. Johnson, authors of the third edition of Modern Technical Writing.<sup>3</sup> These authors suggest that photographs are best used to substantiate the truth. If, for example, a fuel tank has become distorted during field testing, a photograph can provide visual proof of this. However, photographs are limited as illustrations in that they can only show surface views. Drawings, on the other hand, can delineate surface and interior views simultaneously. They also, according to Sherman and Johnson, "make it possible to omit what is not significant and to emphasize what is important."

2.3.12.10. Quality of photographs and drawings. Photographs should be good quality black and white, medium contrast, and reproducible at Army print plants. Line drawings shall contain no unbroken lines. A sufficient weight of lines should be used to prevent deterioration of line quality should the drawing be reduced in size. Shading is not recommended. Further information can be found in MIL-M-38784B and AR 310-3.

2.3.12.11. Use of color. Avoid the use of color if at all possible; a good quality black and white will serve in nearly all photo requirements. Color prints cost more to print due to the number of passes through the press to produce the "color" image. It is also difficult to get true register marks aligned in the press so there is little chance of colors bleeding on to each other. Finally, color images rarely produce the desired effect in the final document.

2.3.13. Headings.

2.3.13.1. General. The same rule applies to subdivisions of headings as applies in outlining: there must be at least two subheadings at any given level. Specific rules governing heading format vary according to report section and heading level. The writer must thus pay close attention to place-

ment, numbering, horizontal and vertical spacing, capitalization, and punctuation.

2.3.13.2. The "General" heading. The capitalized word "General" is used before introductory material at the third and fourth levels when ensuing paragraphs are numbered.

2.3.13.3. General guidelines on unnumbered headings. Headings for the following sections are centered one inch below the top of the page in all caps: NOTICES; SUMMARY; PREFACE; TABLE OF CONTENTS; LIST OF ILLUSTRATIONS; LIST OF TABLES; LIST OF REFERENCES; BIBLIOGRAPHY; GLOSSARY OF TERMS; LIST OF ABBREVIATIONS, ACRONYMS, AND SYMBOLS; INDEX; and DISTRIBUTION LIST. The appendices have separate cover sheets. The lettered appendix heading (for example, APPENDIX A) is printed in all capitals and centered horizontally and vertically. This heading is separated from the centered title of the appendix (also in all capitals) by two blank spaces. If this title runs more than one line, the additional lines are centered under the first. (See APPENDIX A, p. A-1.)

2.3.13.4. General guidelines on numbered headings. Headings in the body of a report are preceded by a minimum of two Arabic numerals--the major section number and a zero, if there are no subheadings. For example, the heading of the first section in the body would be stated as par. 1.0.

2.3.13.5. Major headings in body. The following principles govern the formatting of major headings (also called first-level headings or primary headings). The statement of each major heading begins at the left margin with an Arabic numeral denoting the section number and followed by a period, a zero, and a second period. Two blank spaces separate the heading number and the heading words. All letters in major headings are capitalized. The heading should not be underlined, nor should it be followed by a period. Any text that follows a major heading begins at the left margin after one blank line. Any major headings following are preceded by two blank lines.

2.3.13.6. Secondary headings in body. The following guidelines apply to all secondary headings. Like major headings, secondary headings begin at the left margin with an Arabic numeral denoting the section number and followed by a period. With secondary headings, though, this period is followed by a specific subdivision number, and a second point. The first secondary heading in section one would thus begin with the following: 1.1. Two blank spaces separate the heading's number and the heading words. Unlike the major heading, only the first letters of important words are capitalized here and the entire word group is underlined. The heading is not followed by a period. Any text that follows a secondary heading begins at the left margin after one blank line. One blank line appears between a secondary heading and a preceding major heading or between two secondary headings.

2.3.13.7. Tertiary headings in body. The following guidelines govern the presentation of tertiary (or third-level) headings in technical reports. The statement of the tertiary heading begins at the left margin with the appropriate Arabic numerals of the major and secondary section of which it is

a part. Each of these is, of course, followed by a period. After the second period, the writer states a third Arabic numeral--the number of the third-level subdivision. It, too, is followed by a period. Thus, the first third-level section in the first secondary section of the fourth section of a report would have the following numerical designation--4.1.1. This heading number, as in major and secondary headings, is separated from the heading words by two blank spaces. The first and all other important words are capitalized but the heading is not underlined. The words of the heading are followed by a period and after two blank spaces, by the text of the section unless there are fourth-level headings. Generally one should double-space between the tertiary heading and any one of the following: a secondary heading, another tertiary heading, or a fourth-level heading. If the tertiary heading is the last heading in a major section, two blank lines separate it from the next major heading.

2.3.13.8. Fourth-level headings. Fourth-level headings begin with a statement of the heading number. Flush left, the heading number contains four numbers: the major section number, the secondary section number, the tertiary section number, and the number of the specific fourth-level section. Each of these numbers is followed by a period. The number of this section illustrates a fourth-level heading number. The words of the fourth-level heading are separated from the number by two blank spaces and are followed by a period, two blank spaces and then the text of the fourth-level section. Only the first word is capitalized. Vertical spacing rules governing tertiary headings apply here as well.

2.3.13.9. Headings below the fourth level. No headings below the fourth level should be used.

2.3.13.10. Headings for figures and tables. Headings for figures and tables include the word "Figure" or "Table," of which only the first letter is capitalized. The figure or table section and item numbers are followed by the heading title capitalized as a third-level heading (see par. 2.3.12.4.).

2.3.14. Binding. The reproduced technical report will be securely fastened along the left edge. The usual binding will be side or saddle-wire stitching. Loose leaf, spiral, plastic comb and post bindings will not be used. Cloth back-strip (binding tape) will be used only when it serves a protective purpose (par. 9-1e(3), AR 310-1).

2.3.15. Numbers in the Text.

2.3.15.1. General. As a general rule, numbers should be presented in figures rather than in words. One exception is at the beginning of a sentence. If the number requires no more than one word to state, it may begin a sentence. If at all possible, however, the sentence should be recast. Occasionally it is also acceptable to write out numbers that require no more than a single syllable to state. The GPO Style Manual offers these important guidelines. Rule 12.4. states: "A figure is used for a single number of 10 or more with the exception of the first word of a sentence." Rule 12.5. reads: "Figures are used in a group of 2 or more numbers, or for related

numbers, any one of which is 10 or more. The sentence will be regarded as a unit for the use of figures." Rule 12.6. states: "A unit of measurement, time, or money, which is always expressed in figures, does not affect the use of figures for other numerical expressions within a sentence."<sup>4</sup>

2.3.15.2. Punctuation. The GPO Style Manual offers this advice on the use of commas in long numbers in Rule 12.14: "The comma is used in a number containing four or more digits, except in serial numbers, common and decimal fractions, astronomical and military time, and kilocycles and meters if not more than four figures pertaining to radio."<sup>5</sup>

2.3.15.3. Fractions. Only when fractions stand by themselves or are followed by "of a" or "of an," are they spelled out. In most other cases, especially in unit modifiers (as in  $\frac{1}{2}$ -in. pipe), fractions are stated as figures. The typewriter keys stating fractions should be used; fractions may also be stated as full-sized figures separated by slash marks.

2.3.15.4. Dimensions. Dimensions should be stated in figures. When giving dimensions, the writer should use the appropriate abbreviations to denote proper measurements and should be careful to follow these measurement abbreviations with additional abbreviations such as "lg" for "long," "w" for "wide," and "h" for "high."

2.3.15.5. Numbers and lists. Numbers are used with lists only when one wishes to establish a priority either of importance or sequence among items. This applies to both "run-in" lists (lists in the main text) and indented "set-off" lists (see also par. 3.2.4.). Generally, these item numbers are placed in parentheses and are separated from the item itself by two blank spaces.

## 2.3.16. Pagination.

2.3.16.1. Placement. Page numbers are to be centered at the bottom of the page on a line that is one inch above the page bottom.

2.3.16.2. Notices. No page number is listed at the bottom of the "NOTICES" page. The Notices page is always printed on the inside of the front cover.

2.3.16.3. DD Form 1473, other front matter, body of report, list of references and bibliography. Beginning with the Report Documentation Page (DD Form 1473) pages 1 and 2, report pages are numbered consecutively in ascending Arabic numerals through the bibliography. Section numbers do not precede the page numbers. The DD Form 1473, the Table of Contents, the List of Tables, the List of Illustrations, the first page of the report body (the Introduction), the List of References, and the Bibliography are always right-hand pages even when report pages are printed on both sides. (NOTE: In this style manual, several pages without text contain the statement "THIS PAGE LEFT BLANK INTENTIONALLY." These pages are used to ensure that the tables and lists mentioned above begin on a right-hand page.)

2.3.16.4. Appendices. Pagination in an appendix includes both the capital letter used to designate the appendix and an Arabic numeral. Pages are

lettered and numbered appropriately and consecutively in ascending Arabic numerals beginning with the title page for the Appendix as the first page. Appendices are identified by capital letters: the first appendix is APPENDIX A, the second is APPENDIX B, etc. Thus, the first page in the first Appendix would be designated as "A-1," while the fourth page in a third appendix would be designated as "C-4." A hyphen is placed between the letter and the number. The cover and first page of an appendix are always right-hand pages. If the pages of an appendix are already numbered and the original numbers of these pages are of no use to the reader, the numbers are deleted and the new page numbers are inserted. If both sets of page numbers are needed (and this is rare), the appendix designations (letter and number) are centered directly below the original number. (See APPENDIX A of this manual.)

2.3.16.5. Glossary. A glossary is useful in a report that uses many technical terms that need definitions (see APPENDIX B for aid in writing definitions). Pages in this section begin a new sequence of ascending Arabic numerals, and each numeral is preceded by the capitalized word "Glossary" and a hyphen. Thus, the second page in a glossary would be designated as "Glossary-2." This designation is centered one inch above the bottom of the page.

2.3.16.6. List of abbreviations, acronyms, and symbols. Pages in this section begin a new sequence of ascending Arabic numerals, and each numeral is preceded by the capitalized word "Abbreviations" and a hyphen. Thus, the fifth page in this section would be designated as "Abbreviations-5." This designation is centered one inch above the bottom of the page.

2.3.16.7. Index. An alphabetical index of key terms is often useful in a long report. When it is included, each of its consecutively numbered pages is preceded by the capitalized word "Index" and a hyphen. The pages include a new sequence of numbers beginning with the first page of the index which will be designated as "Index-1." All page designations are centered one inch above the bottom of the page.

### 3.0. PUNCTUATION AND CAPITALIZATION

#### 3.1. General

Rules governing punctuation and capitalization--or what is also called mechanics--ideally help to clarify the meanings of single words and statements. The following paragraphs, therefore, provide specific advice on those areas of mechanics that can cause problems for the technical writer. Certain rules are not treated for one or two reasons: either they rarely apply in engineering report writing (such as those governing apostrophies and quotation marks), or their proper usage is widely known (such as the rule specifying the placement of a period at the end of a sentence). In sum, the rules below do not specify all uses of each punctuation mark and all cases when capital letters are used; they rather point out problem areas.

## 3.2. Punctuation

### 3.2.1. Period.

3.2.1.1. Headings. Periods are used after each number that precedes a heading title. Periods are only used after heading titles when text directly follows the heading title (as in this item).

3.2.1.2. Spaced periods. Spaced periods are used between titles and correspondent page numbers in the Table of Contents, in the List of Illustrations, and in the List of Tables. The first spaced period is placed one space after the last word of the title and the last spaced period is placed in the space immediately preceding the space below the letter "P" in the heading "Page."

3.2.1.3. Abbreviations. Periods are not used after abbreviations unless the abbreviation spells a word. Thus, one would write yd, US, and ft instead of yd., U.S., and ft.; but would write "in." to abbreviate the word "inch."

3.2.1.4. Periods and quotation marks. Periods are always placed inside quotation marks.

3.2.1.5. Periods and parentheses. If the material in a parenthetical statement is a complete sentence and follows a completed sentence, a period is placed inside the second parenthesis, and a period comes at the end of the preceding sentence. If the parenthetical material is a complete sentence and interrupts another sentence, it contains no period. If the parenthetical material is not a sentence and yet comes at the end of another sentence, there is no period following the sentence which precedes it; the period follows the parenthesis.

### 3.2.2. Comma.

3.2.2.1. Numbers. (See par. 2.3.15.2.)

3.2.2.2. Clauses. Comma usage varies with different types of clauses. A clause is a group of words containing both a subject and a verb. Independent clauses can stand by themselves as sentences. Dependent adverbial and adjective clauses must be attached to independent clauses. Commas should be placed as follows: (1) after the first independent clause in a compound sentence (that is, a sentence composed of at least two independent clauses); (2) after an introductory adverbial clause; and (3) both before and after a nonrestrictive (nonessential) adjective clause.

Ex. (1) The engineers studied the needs of the organization, and then they proposed a solution.

Ex. (2) After studying the needs of the organization, the engineers proposed a solution.

Ex. (3) This plastic battery box, which Blowhard helped us design,  
helps us save money.

3.2.2.3. Series. A comma is used after each item in a series preceding the word and.

Ex. Track components in a combat vehicle consist of end connectors,  
center guides, shoes, and connecting pins.

3.2.2.4. Coordinate adjectives preceding a noun. A comma is used to  
separate coordinate adjectives preceding a noun when the "and" is omitted.

Ex. This fast, efficient method should be explored.

3.2.2.5. Introductory participial phrases. A comma is used after an intro-  
ductory participial phrase.

Ex. Designed to replace the metal fuel tanks in 5-ton trucks, these  
plastic tanks are safe and cost-efficient.

3.2.2.6. Conjunctive adverbs. A conjunctive adverb (thus, however, there-  
fore, nevertheless, clearly, and etc.) is (1) followed by a comma when it  
begins a sentence, and (2) set off by commas when it interrupts a sentence.

Ex. However, this procedure is more expensive than rotocasting.

Ex. This procedure, however, is more expensive than rotocasting.

3.2.3. Colon.

3.2.3.1. Colons and lists. A colon is used to introduce a list of items if  
the list is relatively short and is run into the text (either with or without  
numbers). If some priority of sequence or of importance is to be noted, each  
item is preceded by an Arabic numeral beginning with 1. The numbers are  
enclosed in parenthesis. A colon is also used to introduce lists of items  
that are indented five spaces from each margin and preceded by either numbers  
or "bullets" (see par. 2.2.8.). Usually these items are not complete sen-  
tences. When the items are complete sentences, a period is placed at the end of  
the text material before the indented list. (See also par. 3.2.4.)

3.2.3.2. Colon and emphasis. Placing a colon before a list of items cer-  
tainly emphasizes the importance of those items. A colon is also used to  
give emphasis to a sentence following it. Usually the sentence introduced by  
the colon in some way explains or clarifies the information presented in the  
sentence preceding the colon.

3.2.3.3. Colons in proportions and ratios. Single colons are used among  
elements of a proportion (as in a 5:2:1 mixture). Double colons are used to  
show ratios.

3.2.4. Bullets. Listed items are "bulleted" for emphasis. A bullet is  
especially useful when one wishes to list items of equal importance. A

"bullet" is made by typing a lower case o and filling it in. The first two sections of this manual (1.0. and 2.0.) both contain bulleted lists. Use the guidelines below when "bulleting" items.

- Indent the material five spaces from each margin. The sixth space of the first line begins with a bullet followed by two blank spaces (as illustrated here).
- Skip one line space between bulleted items if the items are complete sentences or if they follow a complete sentence (or several lines of text as in Section 1.0.).
- Skip no space between bulleted items if they directly follow headings or other incomplete sentence structures (as in par. 2.2.).

### 3.2.5. Parentheses and Brackets.

3.2.5.1. Parentheses. Parentheses are used to enclose the following: each item number in a list based on sequence of importance, a "list of references" number (see par. 7.2.), a cross-reference instruction containing the word "see" and a heading number, and text material that briefly interrupts the grammatical or logical flow of a sentence.

3.2.5.2. Brackets. Brackets are used to enclose the following: the word "sic" when placed directly after an error in quoted material and mathematics material that is "to be treated as a unit."<sup>6</sup>

3.2.6. Italics. The typewriter equivalent of printed italic type is underlining. The following types of material are underlined: secondary headings and titles of long publications such as books and extended reports, words referred to as words (as in "Capitalize the word 'Table'").

3.2.7. Hyphen. The typed hyphen is used as follows in technical writing: between elements of some compound nouns and unit modifiers (see par. 4.2.), in chemical formulas (see GPO Style Manual, Rules 6.43. and 6.44.), and at the end of a line to indicate word division. Use a double hyphen with no spaces between letters of two words for a dash--instead of a single hyphen with a space on either side.

3.2.8. Degree Sign. Use the degree sign (°) and the word "degrees" as shown in examples:

- 49° below zero
- -15°C
- 45° to 65°F
- 150 million degrees Fahrenheit
- 45° north latitude

- a 45-degree angle
- a polariscopic test of 83°

3.2.9. Odds and Ends. The quotation mark (") should not be used to designate inch(es); use "in." The apostrophe should not be used to designate feet; use "ft" without a period. The pound sign (#) should not be used for either pound or number. The percent sign (%) should not be used; use the word "percent." Use standard alphabetic abbreviations.

### 3.3. Capitalization

3.3.1. General. Section 4 of the GPO Style Manual offers an extensive list of words that should be capitalized.

3.3.2. Capitalization of Headings. (See par. 2.3.13. of this report.)

3.3.3. Capitalization of Proper Names. All proper names and derivatives of proper names unless they have "acquired independent common meaning" (see GPO Style Manual, Rule 3.4.) are capitalized. A common noun used as a shortened form of a clearly specified proper noun is also capitalized (as in using the word "Command" to refer to the US Army Tank-Automotive Command).

3.3.4. Capitalization of Abbreviations. Capitalization of abbreviations should generally follow capitalization of the word or words abbreviated.

## 4.0. ABBREVIATING AND COMPOUNDING

### 4.1. Abbreviating

Spell out the word the first time an abbreviation is used. This is to insure that the audience understands exactly the word being used. MIL-STD-12C (abbreviations for use on Drawings, Specifications, Standards and in Technical Documents) allows the use of the same abbreviation for several words, e.g., G or g is used for girder, glass, glyptal cloth, gravity, grounded (outlet), single glass and gram. Therefore, always spell out the word the first time it is used. Show the abbreviation in parentheses immediately following the word. Then be consistent--use the abbreviation throughout the remainder of the document.

In general, abbreviations for measurement and technical terms will be used without periods. For example: yd, ft, lb; in the case where an abbreviation spells a word, as in inch, use the period, e.g., in. Some common abbreviations are:

# ABBREVIATIONS

abcoulomb	aC	foot-pound	ft-lb
abvolt	aV	force of gravity	g
acceleration of gravity	g	frequency modulation	fm
afternoon	p.m.	gallons per minute	GPM
alternating current	ac	gigahertz	GHz
ampere	A	gram	g
ampere-hour	Ah	gravity	G
ampere-turn	At	gross horsepower	GHP
amplitude modulation	am	gross vehicle weight	GVW
angstrom	Å	gross weight	gr. wt.
atomic weight	at. wt.	Hertz	Hz
audiofrequency	af	high explosive	HE
azimuth	AZ	high frequency	HF
board measure	B.M.	horsepower	HP
boiling point	bp	horsepowerhour	hp-hr
brake horsepower	BHP	inch	in.
brake mean effective pressure	bmeP	inside diameter	ID
brake specific fuel consumption	BSFC	joule	J
British thermal unit	BTU	kilo	k
Celsius, Centigrade	°C	kilogram	kg
center of gravity	CG	kilometer	km
centimeter	cm	kilopascal	kPa
chemically pure	c.p.	kilovoltampere	KVA
circular mil	cir mil	kilowatt	kW
constant velocity	CV	kilowatthour	kWh
cord-foot	cd ft	liter	l
cosine	cos	low frequency	LF
coulomb	C	logarithm	log
cubic	cu	magnetomotive force	mmf
cubic centimeter	cm <sup>3</sup>	maximum	max
cubic feet per minute	CFM	megahertz	MHz
cubic foot	ft <sup>3</sup>	melting point	mp
cubic inch	in <sup>3</sup>	meter	m
cycles per minute	c/m	micro	μ
cycles per second	CPS	microfarad	μf
decibel	dB	micron	μ
decibel unit	dBu	mile	mi
decimeter	dm	miles per gallon	MPG
degrees per second	deg/sec	milli	m
diameter	D	millimeter	mm
direct current	dc	million	M
electromotive force	emf	milli-radian	mr
elevation	EL	millisecond	ms
Fahrenheit	°F	minimum	min
Farad	F	morning	a.m.
field of view	FOV	net weight	net wt.
foot	ft	Newton	N
foot per minute	ft/min	Newton meter	N-m.
foot per second	ft/s	ohm	Ω

# ABBREVIATIONS (continued)

outside diameter	OD	specific fuel consumption	sfc
parts per million	ppm	square centimeter per second	cm <sup>2</sup> /sec
Pascal	Pa	square foot	ft <sup>2</sup>
pound-foot	ft-lb	square inch per second	in <sup>2</sup> /sec
pound-force	lbf	standard cubic feet per minute	SCFM
pound-mass	lbm	steradian	sr
pounds per second	pps	superhigh frequency	SHF
pounds per square inch	psi	thousand	K
pounds per square inch absolute	psia	ultrahigh frequency	UHF
pounds per square inch, gage	psig	very high frequency	VHF
radian per second	rad/sec	very low frequency	VLF
radiofrequency	RF	volt	V
radius	R	volume	vol.
revolutions per minute	RPM	Watt	W
root mean square	rms	wave length	$\lambda$
sine	sin		

## 4.2. Compounding

A compound word is a union of two or more words, either with or without a hyphen. It conveys a unit idea that is not clearly or quickly conveyed by the compound words in unconnected succession. The hyphen in a compound is a mark of punctuation that not only unites but separates the component words, and thus facilitates understanding, aids readability, and insures correct punctuation.

### 4.2.1. General Rules.

(1) In general, omit the hyphen when words appear in regular order and the omission causes no ambiguity in sense or sound.

Examples: banking hours  
patent right  
oil pressure

(2) Words are usually combined to express a literal or nonliteral (figurative) unit idea that would not be as clearly expressed in unconnected succession.

Examples: afterglow  
right-of-way

(3) Unless otherwise indicated, a derivative of a compound retains the solid or hyphenated form of the original compound.

Examples: coldbloodedness  
footnoting  
X-rayer  
Y-shaped

(4) Except after the short prefixes co, de, pre, pro, and re, which are generally printed solid, a hyphen is used to avoid doubling a vowel or tripling a consonant.

Examples: cooperation  
deemphasis  
micro-organism  
ultra-atomic

(5) Print solid two nouns that form a third when the compound has only one primary accent, especially when the prefixed noun consists of only one syllable or when one of the elements loses its original accent.

Examples: airship  
footnote  
locksmith  
crewman

(6) Print solid a noun consisting of a short verb and an adverb as its second element, except when the use of the solid form would interfere with comprehension.

Examples: blowout  
flareback  
markoff  
but cut-in  
run-in  
tie-in

(7) Compounds beginning with the following nouns are usually printed solid.

Examples:	book	house	school	way
	eye	mill	shop	wood
	horse	play	snow	work

(8) Compounds ending in the following are usually printed solid, especially when the prefixed word consists of one syllable.

Examples:	berry	keeper	piece	weed
	blossom	keeping	power	wide
	boat	light	proof	wise
	book	like	room	woman
	borne	maker	shop	wood
	bound	making	smith	work
	brained	man	stone	worker
	bush	master	store	working
	fish	mate	tail	worm
	flower	mill	tight	wort
	grower	mistress	time	writer

(9) Print solid any, every, no, and some when combined with body, thing, and where; when one is the second element, print as two words if meaning a single or particular person or thing; to avoid mispronunciation, print no one as two words at all times.

Examples: anybody everybody somebody  
anything nothing something  
no one someone everyone

4.2.2. Unit Modifiers. Print a hyphen between words, or abbreviations and words, combined to form a unit modifier immediately preceding the word modified, except as indicated in par. 4.2. This applies particularly to combinations in which one element is a present or past participle. Below is a list of rules for using hyphens in unit modifiers.

(1) Do not use a hyphen in a unit modifier consisting of two nouns.

Examples: gust front conditions  
storm research programs

(2) Use a hyphen in a unit modifier consisting of an adjective and a noun or a noun and an adjective.

Examples: dual-wavelength radar  
above-average frequencies  
part-load operations  
full-load performance

Exception: Print without a hyphen a two-word modifier the first element of which is a comparative or superlative, e.g., higher level decision.

(3) Use a hyphen in a combination of color terms used as a unit modifier.

Example: Silver-gray body

(4) Use a hyphen in a combination that contains numbers.

Examples: three-dimensional model  
two-axis anemometer

(5) Use a hyphen when a connecting word is implied.

Examples: north-south alignment  
air-sea interaction  
winter-fall maxima

(6) Use a hyphen in an improvised compound containing a verb, or three (or more) words.

Examples: jack-up capability  
cloud-to-ground strokes  
roof-to-wall connection

(7) Use a hyphen in a unit modifier containing a present or past participle (or words in -ed and -ing forms).

Examples: broad-based support  
river-crossing maneuvers  
many-faceted research

(8) Do not insert a hyphen in a proper name, but use a hyphen when the phrase is used generically.

Example: Severe Thunderstorm Watch  
but severe-thunderstorm watch

(9) Do not use a hyphen in a unit modifier containing an adverb ending in -ly. Use a hyphen in those containing the adverb well, still, or ever.

Examples: well-kept laboratory  
still-new dynamometer

Exception: Do not use a hyphen even with those words when they are modified by another adverb, e.g., very well kept laboratory.

(10) Do not use a hyphen in a two-word unit modifier, the first element of which is an adverb ending in "ly."

Examples: eagerly awaited moment  
wholly owned subsidiary  
externally mounted gun

4.2.3. Technical Terms. Print a hyphen between the elements of technical compound units of measure.

Examples: passenger-mile  
kilowatt-hour  
horsepower-hour

4.2.4. Numeric Compounds. Use a hyphen between elements of compound numbers from twenty-one to ninety-nine and in adjective compounds with a numeric element first.

Examples: twenty-one  
twenty-first  
24-inch ruler  
8-hour day

4.2.5. Fractional Numeric Compounds. Use a hyphen between the elements of a fraction, but omit it between the numerator and denominator when the hyphen appears in either or both.

Examples: one-thousandth  
two one-thousandths  
three-fourths of an inch  
two-thirds  
twenty-one thirty-seconds

4.2.6. Capital Letter Words. Use a hyphen to join a single capital letter to a noun or participle.

Examples: H-bomb  
I-beam  
V-necked  
X-ray  
T-shaped  
T-square  
V-blade

4.2.7. Improvised Words. Print a hyphen between elements of an improvised compound.

Examples: blue-pencil  
state-of-the-art  
18-year-old  
know-how

## 5.0. SPELLING

### 5.1. Spelling Called for by Government Printing Office Style Manual

In general, the preferred spelling of Webster's International Dictionary is to be followed.<sup>7</sup> Items listed here either indicate spelling peculiar to the Army (called for by the GPO Style Manual) or items generally misused in manuscripts.

Affect, effect:

- affect - denotes influence, operation, action upon, concern.  
Always a verb.

Ex. This adjustment affects the length of clutch pedal free travel.

- effect - denotes consequence of result (noun); bring about, carry out, fulfill (as a verb).

Ex. Noun: The effect of PM will be this: Your truck will be ready to go.

Verb: This rule will effect a change.

Align - this is correct. Do not spell it "aline."

All right - not alright.

Dipstick - is spelled as one word.

Disk - is the preferred spelling. Do not use disc.

Fuse - to denote melting together or an electrical safety device.

Fuze - is the device used to initiate detonation or to start flame.

Gage - is the preferred spelling. Do not use "gauge."

Insure - preferred spelling. Do not use "ensure."

Material - parts, goods, or stock of which anything is composed or made.

Materiel - supplies, stores and equipment of all types used by Armed Forces including instruments, vehicles, clothing and ammunition.

Permissible - not permissable.

Pickup - referring to a type of truck.

Pick-up - a noun denoting action.

Power-takeoff - the word "takeoff" when used with "power" is one word.

Tailgate - is spelled as one word.

Taillight - is spelled as one word.

Time frame - is spelled as two words.

## 5.2. Words Easily Misspelled

This section presents, clearly and succinctly, the basic information about some of the most commonly misspelled words.

5.2.1. Double Consonants. A single consonant following a single vowel and ending a monosyllable or a final accented syllable is doubled before a suffix beginning with a vowel.

Bag, bagging, bagged.

Corral, corralling, corralled.

Occur, occurring, occurred.

Permit, permitting, permitted.

Red, reddish.

Refer, referring, referred (but not reference).

Auxiliary (only one "l").

Control, controlling, controlled.

Generally.  
Level, leveling, leveled.  
Parallel, paralleling, paralleled.  
Travel, traveling, traveled.  
Cancel, canceling, canceled.  
Label, labeling, labeled.

If the accent in a derivative falls upon an earlier syllable than it does in the primitive, the consonant is not doubled.

Refer, reference.  
Prefer, preference.  
Infer, inference.

#### 5.2.2. Endings "cede," "ceed," and "sede."

Only one word ends in "sede" (supersede).

Only three words end in "ceed" (exceed, proceed, and succeed). All other such words end in "cede" (precede, secede, etc.).

### 6.0. READABILITY

#### 6.1. Standards (DARCOM-P 310-10 and DA Cir 310-9)

The standards described in the above listed documents are part of a long-range program to improve the Army publications system. The policy, through the use of "small words and phrases," is designed to improve the readability of publications by preparing the message in understandable and usable language. Both documents contain a list of small words or phrases you can use rather than a sometimes more obtuse polysyllabic word.

#### 6.2. Word Choice

6.2.1. Using Simple Language. Official writing does not demand big words or fancy phrases. Write naturally--in the words you use to speak. The sense and strength of English is in its small, often one-syllable words. Not only do they save preparation time, they improve the vigor of your writing and the clarity of your ideas.

<u>Instead of</u>	<u>Try</u>
accomplish	carry out
accordingly	so
actual	real, true
as a result of	because of
consideration should be given to the fact that	note, or note that

despite the fact that  
 due to the fact that  
 facilitate  
 goes without saying  
 in accordance with  
 in order to  
 in regard to  
 in view of the fact that  
 perform  
 provided that  
 regarding  
 render  
 therefore  
 there are (there is)  
 until such time as  
 used for fuel purposes  
 (the) use of  
 utilize, utilization  
 viable

although, though  
 due to, since  
 ease, help  
 (unnecessary - leave out)  
 with, or per  
 to  
 on, about, concerning  
 because, as  
 do  
 if  
 about, of, on  
 give, make  
 so  
 (leave out)  
 until  
 used for fuel  
 (leave out)  
 use  
 workable

#### 6.2.2. Avoiding Word Confusion Errors.

all ready (prepared)  
     already (previously)  
 all together (collectively)  
     altogether (completely)  
 awhile (for some time)  
     a while (a short time)  
 ascent (rise)  
     assent (consent)  
 born (birth)  
     borne (carried)  
 capital (city)  
     capitol (building)

casual (unimportant)  
     causal (resulting)  
 complement (completing)  
     compliment (praise)  
 councilor (of council)  
     counselor (advisor)  
 device (gadget)  
     devise (plan, contrive)  
 discreet (prudent)  
     discrete (distinct)  
 dyeing (coloring)  
     dying (ceasing to live)

elicit (to draw)	perquisite (privilege)
illicit (illegal)	prerequisite (requirement)
envelop (to wrap up or in) (v.)	personal (individual)
envelope (the wrapper) (n.)	personnel (staff)
expose' (a revealing) (n.)	perspective (view)
expose (to lay open) (v.)	prospective (expected)
farther (distance)	precedence (priority)
further (not distance)	precedents (usage)
indict (to accuse)	principal (chief)
indite (to compose)	principle (proposition)
inequity (unfairness)	sometime (formerly)
iniquity (sin)	some time (some time ago)
ingenious (skillful)	sometimes (at times)
ingenuous (simple)	spacious (space)
mil (1/1000-inch)	specious (plausible)
mill (1/1000 dollar)	stationary (fixed)
preemptory (decisive)	stationery (paper)
preemptory (seizing)	

### 6.2.3. Overworked Words and Phrases to Avoid in Writing.

effect, effected (as a verb)  
 focal point  
 ideal, ideally  
 immeasurable  
 implement(ed) (as a verb)  
 render  
 unacceptable  
 vital  
 vast  
 very  
 extremely  
 excellent  
 commence  
 reflect  
 image  
 finalization  
 to include (including)

### 6.3. Sentence Structure and Grammar

Sentences, not words, are the essence of writing, just as equations and functions, and not bare numbers, are the real guts of mathematics. Most English sentences are made with a subject, verb and direct object. The subject is a noun or a noun equivalent (pronoun, noun clause, gerund, infinitive) that is the starting point of the statement. A verb is a word that has forms (like go, goes, gone, going) and in a sentence agrees with the subject. In a typical sentence, the verb follows the subject and, like the subject, is often the nucleus for modifying words. The direct object of a verb is a word or group of words, usually following the verb, that names the recipient of the

act expressed by the verb. It answers the question asked by adding "what" or "whom" after the verb. The complement is a noun or adjective in the predicate which follows a linking verb. In contrast to an object, a complement is related to the subject rather than the verb, for it follows verbs expressing condition rather than direct action. The typical order of the main sentence elements is subject, verb, object (or subject-linking verb-complement) and is the order in which we make most statements and the means by which we understand them.

6.3.1. Tense. The subject of a sentence or clause determines the verb form that goes with it. Correspondence between subject and verb is called agreement. English verbs have six tenses: past, present, future, past perfect, present perfect, and future perfect. Tense of verbs must be consistent with the subject of the sentence and with other verbs in a passage. By using different tenses, a writer sets the time of the situation he is describing, and also indicates for the reader the continuity of the action or explanation. It is important that the verb tenses are consistent and easy to follow. Use of the proper verb tense is essential if the reader of a Technical Report is to know if events being discussed have happened, are happening now, or will happen sometime in the future. Here are some guidelines to follow when preparing a report:

- The aim of the introduction is to provide a definition of the work effort to be discussed and background concerning circumstances and events which prompted the work. Thus, the introduction deals almost exclusively with events in the past and, with the exception of such statements as "the purpose of this report is \_\_\_\_\_," should be written in the past tense.
- The main body, summary, and conclusions of the report have one thing in common: They all deal with what has already taken place (completion of laboratory or field tests, etc.) and should also be expressed in the past tense.
- Present and future tense verb forms are appropriate for that portion of the report dealing with recommended future courses of action.

6.3.2. Voice. In scientific writing, the whole point is to emphasize the action taken and downplay the person who did it. English grammar has two voices (of the verb)--active and passive. A verb in the active voice is a normal, simple-type verb that emphasizes the person performing the action: i.e., "he" runs dynamometer tests. The passive consists of a form of "to be" plus the past participle: i.e., dynamometer tests are run (by him). Passive verbs are natural if the subject is unknown or unimportant. And we've just said that in scientific writing, the performer is unimportant to the experiment or project.

Therefore, it is not advisable to use personal pronouns. This will force writers into heavy use of the passive voice, and thereby, preparing a Technical Report describing events and actions rather than stressing the importance of the individual who performed the various tasks. It should be

pointed out, however, that exclusive use of the passive voice is not a hard-and-fast rule. Limited use of active voice will help to make what otherwise might be dull subject-matter, more appealing to the reader.

6.3.3. Parallel Elements. One way to clarify and simplify your message is by being consistent with the use of parallel elements. Where there are two items of the same type in a sentence or paragraph, the structure of the items should be as similar as possible. Conjoined items (linked by "and") in a list should be of the same type and have the same structure.

6.3.4. Emphasis. The proper place in the sentence for the word or groups of words that you want to make most prominent is usually at the end. The other prominent position in the sentence is the beginning. Any element in the sentence other than the subject becomes emphatic when placed first. An important principle in good writing is always to make sure that the proper place for that which the writer wants to emphasize is at the end of: a sentence, sentences of a paragraph, and the paragraphs of a composition.

6.3.5. Wordiness. Good writing is concise. A sentence should contain no unnecessary words, a paragraph no unnecessary sentences, and a composition no unnecessary paragraphs. This requires that the writer make every word tell. It does not mean he should make all his sentences short, or omit detail and treat his subject only in outline. The writer should question every word. If it doesn't carry its weight, don't use it.

Example: The use of "of" in such sentence construction as "all of the samples" or "some of the units" serves no useful purpose. The word "of" adds nothing to the main idea. A better way would be: "all the samples or some units."

6.3.6. The Complexity of a and an. The correct use of the indefinite articles a and an causes considerable confusion among writers. To standardize usage in writing, the following rules are recommended.

Ex. 1 Use a before:

- words beginning with consonant sounds:  
a cannon, a book
- words spelled with vowels, pronounced like consonants:  
a one-hour class, a 1,000 HP engine
- words with a pronounced initial h:  
a hat, a horse
- words beginning with a long "u" sound:  
a used car, a university
- abbreviations or acronyms pronounced as a word:  
a SALT treaty, a TACOM employee

- number collectives and some numbers:  
a dozen, a hundred
- letters individually pronounced and whose pronunciation when spelled out would have a consonant sound (for example, the letter "Q" pronounced "kyoo"):  
a Z, a B

Ex. 2 Use an before:

- words beginning with a vowel sound:  
an apple, an oval
- words beginning with a silent, or unstressed "h":  
an honor, an hour
- letters individually pronounced and whose pronunciation when spelled out would have a vowel sound (for example, the letter "F" pronounced "ef")  
an F, an H, an HEW office, an M1 tank

## 7.0. DOCUMENTATION

### 7.1. Using Footnotes

Place the footnote number immediately following and half a line above the quoted or paraphrased material, as shown in the example:

Example: . . . . . pertaining to radio."<sup>3</sup>

7.1.1. In the Text. Footnotes in the text are numbered consecutively from 1 to 99, and then begin with 1A1 to 1A99. The footnotes are to be listed on a separate page at the end of the document. The separate page will be titled "List of References." In the event there are less than four footnotes in the report, they may appear on the same page as the material referenced rather than on a "referenced" page. When footnotes are on the same page as the referenced material, a cutoff dash is required between the text and footnote. This dash starts two spaces below the text at the left margin stop and is 1½ inches long. If two or more footnotes apply to the same page, double-space between each footnote.

7.1.2. In Tables. Footnotes to table material are numbered independently from footnotes to the text. Each table will carry its own footnote numbering sequence (see par. 2.3.11.10.). Footnotes are to appear in block style with the author's last name first, "title" of the source, publisher, publisher's geographical location, page number, and (date). Footnotes will be divided from the text of the table by a cutoff line 1½ inches long starting at the left margin of the table. If two or more footnotes apply to the same table, double-space between each footnote.

## 7.2. Preparing the "List of References"

The List of References is the list of footnotes from the text. Entries are listed in numerical order as cited in the text. This is always a separate page at the end of the report.

The format for footnotes will show the sequence number raised half a line, the author (last name first), "title" (in quotes), publisher, publisher's geographical location, page, and (date). See below and p. 55.

- <sup>1</sup> Wallace, J.D. and Holdings, J.B., "Guide to Writing and Style,"  
Battelle Memorial Institute, Columbus, OH, p. 79, (1966)

## 7.3. Including a Bibliography

A bibliography is a list of selected sources the writer consulted to complete the project. This is arranged alphabetically by author's last name. When the author's name is not available, the title of the work is listed first, in the same alphabetical order. In some ways, a bibliography repeats the information contained in the footnotes (or material on the "Reference" page); however, it provides the reader with an alphabetical index for quick reference. It lists not only footnoted sources, but all sources consulted. The entries include books, newspaper and magazine articles, research reports, etc.

Each entry is single-spaced, the second and all subsequent lines are indented five spaces, and double spacing separates individual entries (see p. 57). Examples are as follows:

- Lannon, John M., "Technical Writing," Little, Brown  
and Company, Boston, MA (1979)
- MIL-STD-847B, "Format Requirements for Scientific and  
Technical Reports Prepared by or for Department of  
Defense," (1983)
- "Lightweight Tow Bars," Army Research, Development &  
Acquisition Magazine, (November-December 1981)

## 7.4. Including an Index

An index is not required, but for some long reports (over 50 pages) it may be desirable. If used, the index should list pertinent subjects under every topic for which users are likely to look. Topics are listed alphabetically. The index is to be constructed to enable the user to locate easily any part, information, or topic in the text.

## 7.5. Security Marking Documentation

The following information was taken from AR 380-5, DOD Security Information Program Regulation, for safeguarding classification information.

Four symbols are used most often when marking classified documents.  
These are:

(TS) for Top Secret  
(S) for Secret  
(C) for Confidential  
(U) for Unclassified

Whenever a symbol is used, it must appear in parenthesis.

### Titles

A title shall be marked by placing the classification symbol immediately following and to the right of the item. Examples:

5.0. LOCATION OF TESTING(U)

5.1. Location of Testing.(U)

### TABLE OF CONTENTS

Section	Page
2.3.3. Location of testing.(U). . . . .	6

### Sections or Paragraphs

Each section or paragraph will be marked with the appropriate classification symbol placed immediately following that portion's number, or in the absence of a number, the symbol will go at the start of the paragraph. Examples:

5.2.2.(U) The engine was tested . . .

(U)The engine was tested . . . . .

### Illustrations, Photographs, Figures, Graphs, or Drawings

These shall all be marked by putting the appropriate symbol immediately before the caption. Example:

Figure 1-3. (U)Tracks Used on Vehicles Tested.

Consult AR 380-5 for any further reference information.

### 8.0. EDITING

The Technical Editorial Office is to make sure that technical reports clearly convey and effectively document objectives, conclusions, recommendations, materials and methodology of engineering projects. The authors and typists,

no matter how competent in their fields, cannot be expected to produce a report according to particular editorial standards. The editor (through training, natural talent or both) is a master of the English language, and is sensitive to the consistency in format, abbreviations and detail. The author, or technical reviewer, verifies technical accuracy; the editor insures that the material presents the author's ideas clearly and concisely. Therefore, no matter whether the manuscript is produced by in-house writers or by contractors, it is to be edited by people familiar with the types of regulations and recommended practices given in this manual.

Contract monitors, therefore, should be reminded that when a formal report is required, the contract must include provisions (and funding) for a preliminary draft, to allow for editorial changes and final printing.

### 8.1. Relationship between Editor and Writer

The editorial review, then, is the first step on the road to a finished product. The editor must insure that the specific rules and policies (MIL-STD-847B) are followed concerning the elements of a report. The editor's first concern, however, is to help an author produce an excellent report. This concern requires the editor to attend to many small details (requiring copy editing) and to various larger considerations (requiring content editing or rewriting). While straight grammatical editing--for spelling, punctuation and sentence structure--is necessary, the editor is also concerned with the larger things: making a report as good as possible, and helping the author to be a better writer.

Good relations between the author and the editor are essential to produce a good report. As with any relationship between two people, each party must take responsibility for making the relationship work. If one party is uncooperative, the other job becomes very difficult. Just as editors are language experts, authors are technical experts. They must be the final judges of the content of their report, assuring completeness, accuracy, and relevance. An editor may always suggest changes, but the author must take the final responsibility for the technical content. For both parties to obtain their goal--an excellent report--good relations are essential.

The editor who is without specific technical knowledge should be wary of making arbitrary changes in language that might change technical meaning. An editor might make a lovely sentence out of an awkward one by repositioning clauses and phrases; when this is done, however, technical meanings might be changed. The editor should make certain, by question marks or lists of questions with page numbers, that the author sees every major change.

Likewise, the author must read both the edited manuscript and any proof copies with great care to make sure errors do not creep in. It is important for the author to check all numbers, whether statistics, references to figures, tables, or footnotes. Tedious though it may be, this task is vital, and this is the time for changes, not later after the report is printed.

## 8.2. Relationship between Editor and Typist

Most of the marks on the manuscript are formatting instructions to production people, i.e., typists and word processor operators, and are, therefore, not substantive changes. Usually these marks indicate formatting errors. Formatting procedures are found in par. 2.3. in this report. Standard proofreading symbols used by the technical editor are found in par. 8.3. It is essential that both the production people and the technical editors become extremely familiar with proofreading symbols.

By using these symbols consistently, both the editor and the production people will be able to finalize the report and achieve the goals for which the report is written. These goals are to make it clear, concise and complete, correct and technically accurate.

## 8.3. Proofreading Symbols

In reviewing a manuscript, the technical editor will use the conventional proofreading marks. Shown below are the marks most often used. They should be legibly written in the margin and the place of the desired correction should be clearly marked in the text.

- (1) Missing punctuation--insert it.

e.g. The period is missing<sub>o</sub>

e.g. In this case<sup>^</sup> the comma is missing.

- (2) Incorrect punctuation--cross it out and insert correct punctuation.

e.g. After I wrote the sentence~~x~~<sup>^</sup> I proofread it.

- (3) Misspelled or mistyped words--cross out or circle and write in correction.

e.g. This word is <sup>SP</sup> mispelled misspelled

- (4) To delete a word, use ~~—~~.

e.g. Please file the ~~the~~ report.

- (5) Word lined out in the text, you want to let it stand.

e.g. Let it stand--used in the margin. STET



e.g. Let it stand--used in the text. — — — —


(6) Lower case a letter by drawing a diagonally slanted line through it.


e.g. The ~~l~~ar won't start.


(7) Capitalize a letter by underlining it with three strokes.

e.g. We work for the federal Government.

(8) Close up a space by using  or .

e.g. Please lock the car when ever you leave.


(9) Insert a space by using .


e.g. The truck will be here later.


(10) To indicate a new paragraph, use .


(11) To insert a missing word--use a caret.


e.g. The <sup>card</sup>is on table.


(12) Transposed letters or words, use .

e.g. The truck is on the ~~rad~~.

(13) To move copy left, use .

e.g.  Use a left facing bracket to move copy left.

(14) To move copy right, use .

e.g. Use a right facing bracket to move copy right.

THIS PAGE LEFT BLANK INTENTIONALLY

## LIST OF REFERENCES

- 1 Lannon, John M., "Technical Writing," Boston, MA: Little, Brown and Company, (1979)
- 2 US Government Printing Office Style Manual, Rev Ed, Washington, US Government Printing Office (1973)
- 3 Sherman, Theodore S., and Johnson, Simon S., "Modern Technical Writing," 3d Ed, Englewood Cliffs, NJ, Prentice-Hall, Inc. (1975)
- 4 US Government Printing Office Style Manual, Rev Ed, Washington, US Government Printing Office (1973)
- 5 US Government Printing Office Style Manual, Rev Ed, Washington, US Government Printing Office (1973)
- 6 MIL-STD-847B, "Format Requirements for Scientific and Technical Reports Prepared by or for Department of Defense," (1983)
- 7 Webster's "Ninth New Collegiate Dictionary," G. C. Merriam Company, Springfield, MA (1983)

THIS PAGE LEFT BLANK INTENTIONALLY

## SELECTED BIBLIOGRAPHY



- AR 70-31, "Research and Development Standards for Technical Writing,"  
HQ, Dept of Army, (1966)
- Boblenz, James N., "Tank-Automotive R&D Center Laboratory Technical Report  
Style Manual," US Army Tank-Automotive Command Warren, MI (1981)
- Collier, Barbara S. and Joes, E. Ellen, "Guides to ERADCOM Formal Reports,"  
US Army Electronics Research and Development Command, Adelphi, MD (1979)
- Gunning, Robert, "Techniques of Clear Writing," McGraw-Hill Book Company  
(1968)
- Government Printing Office Style Manual, Rev Ed, Washington, D.C.,  
US Government Printing Office
- Hays, Robert William, "Principles of Technical Writing," Addison-Wesley,  
Reading, MA (1965)
- Lannon, John M., "Technical Writing," Little, Brown and Company, Boston,  
MA (1979)
- Mazzatenta, Ernest, "Reporting Your Research: A Handbook for the Researcher  
Writer," General Motors Research Laboratories, GMR-349, Warren, MI (1980)
- MIL-M-38784A, "Military Specification, Manuals, Technical: General Style and  
Format Requirements"
- MIL-STD-12C, "Military Standard Abbreviations for use on Drawings,  
Specifications, Standards, and in Technical Documents"
- MIL-STD-847B, "Format Requirements for Scientific and Technical Reports  
Prepared by or for the Department of Defense," (1983)
- Sherman, Theodore S. and Johnson, Simon S., "Modern Technical Writing," 3rd  
Ed, Prentice-Hall, Inc., Englewood Cliffs, NJ, (1975)
- Strunk, William, Jr. and White, E. B., "Elements of Style, The," 3rd Ed,  
Macmillan Publishing Company, New York, NY, (1979)
- TACOM Suppl 1 to AR 70-31, "Research, Development, and Acquisition Standards  
for Technical Writing," US Army Tank-Automotive Command, Warren, MI  
(1981)
- Technical Report Format Guide, Battelle Project Management Division, Battelle,  
Columbus, OH (1982)
- Wallace, John D. and Holding, J. Brewster, "Guide to Writing and Style,"  
Battelle Memorial Institute, Columbus, OH (1966)
- Webster's Ninth New Collegiate Dictionary, G.C. Merriam Company, Springfield,  
MA

THIS PAGE LEFT BLANK INTENTIONALLY

APPENDIX A

SAMPLE REPORT

THIS PAGE LEFT BLANK INTENTIONALLY

  
 **LABORATORY**  
**TECHNICAL REPORT**

NO. 12657

LIGHT-WEIGHT SADDLE TANK DEVELOPMENT

PHASE I-FABRICATION AND MATERIAL

FEASIBILITY TECHNOLOGY

CONTRACT DAAK30-78-C-0122

JULY 1982

Hollowform, Inc.  
Buckeye International, Inc.  
6345 Variel Ave.  
Woodland Hills, CA 91364  
and Dorothy McClendon  
US Army Tank-Automotive Command  
ATTN: AMSTA-RSC  
Warren, MI 48090

by

Test and Evaluation Document distribution  
limited to US Government agencies only.  
Other requests for this document must be  
referred to TACOM, ATTN: AMSTA-TS



**U.S. ARMY TANK-AUTOMOTIVE COMMAND  
RESEARCH AND DEVELOPMENT CENTER  
Warren, Michigan 48090**

# NOTICES

(Always typed inside front cover)

This report is not to be construed as an official Department of the Army position.

Mention of any trade names or manufacturers in this report shall not be construed as an official indorsement or approval of such products or companies by the US Government.

Destroy this report when it is no longer needed. Do not return it to the originator.

UNCLASSIFIED


SECURITY CLASSIFICATION OF THIS PAGE

## REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Test & Evaluation Document distribution limited to US Gov't agencies only.		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) 12657			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION US Army Tank-Automotive Command, R&D Center		6b. OFFICE SYMBOL (If applicable) AMSTA-RS	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) Warren, MI 48090			7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
					WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) Light-Weight Saddle Tank Development, Phase I-Fabrication and Material Feasibility Technology					
12. PERSONAL AUTHOR(S) Hollowform, Inc., Woodland Hills, CA and Dorothy McClendon, AMSTA-RS					
13a. TYPE OF REPORT Progress		13b. TIME COVERED FROM _____ TO Jul 82		14. DATE OF REPORT (Year, Month, Day) 82 Jul	
15. PAGE COUNT 30					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Fuel Tanks, Polyethylene, Cross-linked, Rotationally molded, Fabrication		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>This program was initiated to develop the capability in manufacturing a fuel tank which will not corrode, be lighter in weight, and last the life of the vehicle. The material to be utilized was high-density polyethylene material.</p> <p>Fabricated tanks will undergo testing at TECOM test sites and assessments will be made.</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Dorothy McClendon			22b. TELEPHONE (Include Area Code) X45920		22c. OFFICE SYMBOL AMSTA-RS

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE



UNCLASSIFIED  
SECURITY CLASSIFICATION OF THIS PAGE

## TABLE OF CONTENTS

Section	Page
1.0. INTRODUCTION . . . . .	9
2.0. OBJECTIVE. . . . .	9
3.0. CONCLUSIONS. . . . .	9
4.0. RECOMMENDATIONS. . . . .	9
4.1. <u>Aluminum Molds</u> . . . . .	9
4.2. <u>Sulfonated Tanks</u> . . . . .	9
4.3. <u>Perforated Step-Plate</u> . . . . .	9
4.4. <u>Standardized Connections</u> . . . . .	9
4.5. <u>Further Recommendations</u> . . . . .	10
5.0. DISCUSSION . . . . .	10
5.1. <u>Background</u> . . . . .	10
5.2. <u>Design</u> . . . . .	10
5.3. <u>Material Selection</u> . . . . .	13
5.4. <u>Fabrication and Tooling</u> . . . . .	13
5.5. <u>Testing</u> . . . . .	15
ADDENDUM . . . . .	16
LIST OF REFERENCES . . . . .	23
DISTRIBUTION LIST. . . . .	Dist-1

THIS PAGE LEFT BLANK INTENTIONALLY

## LIST OF ILLUSTRATIONS

Figure	Title	Page
5-1.	Plastic Fuel Tank For 2½-Ton Truck . . . . .	11
5-2.	Plastic Fuel Tank For 5-Ton Truck . . . . .	12

THIS PAGE LEFT BLANK INTENTIONALLY

## LIST OF TABLES

Table	Title	Page
5-1.	Physical Properties of Marlex, CL-100. . . . .	14
5-2.	Drop Impact of a Molded Container. . . . .	14

THIS PAGE LEFT BLANK INTENTIONALLY

## 1.0. INTRODUCTION

This final technical report, prepared by Hollowform, Inc., for the US Army Tank-Automotive Command under Contract DAAK30-78-C-0122, describes Phase One in the development and testing of safe, cost-efficient plastic fuel tanks. Designed to replace the single metal fuel tank on the 2½-ton truck and the metal saddle tank on the 5-ton truck, these plastic tanks do not corrode or crack in normal wear and significantly reduce the possibility of rupture under stress. In addition, their lighter weight, space-saving designs, and energy-efficient fabrication process make plastic tanks more economical than existing metal tanks.

## 2.0. OBJECTIVE

The primary goal was to design and fabricate plastic fuel tanks that, when tested, would prove superior to the metal tanks currently used on 2½- and 5-ton trucks.

## 3.0. CONCLUSIONS

Further improvements in design and in fabrication procedures will allow us to effectively replace metal tanks currently used on 2½- and 5-ton trucks with plastic versions.

## 4.0. RECOMMENDATIONS

### 4.1. Aluminum Molds

The molds should be made of cast aluminum with shot-peened texture and should incorporate appropriately located, molded-in ribs and corner radii to maintain the tank shape as installed, thereby eliminating negative fuel-weight and side-wall pressure effects.

### 4.2. Sulfonated Tanks

Steps should be taken which will permit us to sulfonate the tanks internally.

### 4.3. Perforated Step-Plate

The incorporation of a perforated step-plate as a part of the tank design on the 2½-ton truck deserves further evaluation so that production costs can be reduced.

### 4.4. Standardized Connections

The feed, supply, return, and vent connections of the 2½- and 5-ton truck tanks should be standardized. This will permit a common fitting to be used and then appropriately reduced to the required pipe size by way of a "close

reducing bushing." This special collar fitting includes a locknut, washer, and gasket, and is similar to what is known as a "tank adapter." Cost savings will be achieved and the seal will be improved.

#### 4.5. Further Recommendations

Recommendations derived from additional field testing should be considered in the final design and fabrication phase.

### 5.0. DISCUSSION

#### 5.1. Background

Metal fuel tank are currently used on 2½- and 5-ton trucks. The tank on the 2½-ton truck weighs 115 lbs and measures 19½ in. high, 30 in. long, and 28 in. deep. Each saddle tank on the 5-ton truck weighs 128½ lbs and measures 17½ in. high, 32½ in. long, and 27½ in. deep. These tanks, however, have distinct disadvantages:

- Corrosion - metal tanks corrode as a result of environmental conditions (humidity cycling in storage) and fuel degradation (chemical/microbial).
- Impact resistance - metal tanks frequently rupture at pressures under 4 psig.
- Cracking - weld-zone stress in metal tanks occasionally results in cracking.
- Heat resistance - metal tanks often explode during fires due to high thermal conductivity.
- Leakage - metal fuel tanks frequently leak at pressures under 4 psig.

Such problems can be eliminated or significantly minimized by replacing metal fuel tanks with plastic versions.

#### 5.2. Design

The plastic fuel tanks were generally designed with dimensions identical to those of the current metal tanks so that transition would be easy. However, several minor modifications were made. One of these changes involved securing the plastic tank. First, grooves (as shown in Figures 5-1 and 5-2) were provided for the existing mounting straps. Tank slippage caused by sudden movement was thereby reduced. In addition, to compensate for the difference in strap location on the sides of the chassis, the groove width was increased. A more significant modification was made in the filler assembly and fill cap designed for the plastic tanks. Because using different hardware on the 2½- and 5-ton truck tanks is inefficient, a single design was adopted for both plastic tanks. The design chosen was that used on the ¼-ton




Figure 5-1. Plastic Fuel Tank for 2½-Ton Truck (Plastic Version of P/N RCSK 5701)




Figure 5-2. Plastic Fuel Tank for 5-Ton Truck (Plastic Version of P/N 19207-11669354)

truck. Not only did this substitution standardize parts, but it also provided a cap that could be easily removed in all climates. In addition, the component filler-neck assembly was modified to provide a flange for the stud mounting on the plastic tank, and the fitting hardware was designed so that the plastic would only be subjected to compressive loads since it exhibits "cold-flow" characteristics.

Molded-in ribs, which parallel the strap grooves, are needed to carry weight to the tank side-walls and thereby prevent tank deformation and resultant fuel-gage inaccuracy. This feature was not incorporated because no suitable location for the ribs could be found.

### 5.3. Material Selection

After evaluating numerous types of rotational-mold polyethylene materials and discovering that nylon materials are included to be brittle, the customer specified that cross-linked polyethylene be used. The tanks were thus molded using Marlex CL-100, dark green, manufactured by Phillips Petroleum Co. The physical properties and impact resistance of parts fabricated from this material are provided by Phillips Petroleum and delineated in Table 5-1 and Table 5-2. Specifically, Table 5-2 reveals the impact the container can withstand without leaking.

In addition to the benefits gained from such properties, tanks made of Marlex CL-100 offer significant weight savings. At 37 lbs, the 55-gal tank designed for the 2½-ton truck weighs 68 percent less than the existing metal tank while at 36½ lbs, the 58-gal tank developed for the 5-ton vehicle offers a weight savings of 72 percent. These weight savings should result in improved fuel economy.

Finally, unlike metal tanks, tanks constructed of cross-linked polyethylene are subject to neither corrosion nor contamination.

### 5.4. Fabrication and Tooling

Currently, two types of molding--blow-molding and rotational-molding--are used to produce one-piece hollow vessels such as fuel tanks. Although the shorter molding-cycle time of the blow-molding process results in lower part costs where high volume is demanded, the rotational molding process was adopted for a number of reasons:

- o The product is totally stress-free;
- o Materials suitable for this process have superior physical properties;
- o Tooling cost for small volume production is low;
- o Mold-tooling lead time is relatively short; and
- o Wall thickness is uniform.

Table 5-1. Physical Properties of Marlex CL-100\*

Property	ASTM Test	Value
Density of the Cross-Linked Product, gms/cc	D1505-68	0.930-0.933
Environmental Stress Cracking Resistance, Condition A, F50, hrs	D1693-70	1000
Tensile Strength, Ultimate, psi 2 in./min	D638-72 Type IV Specimen	2600
Elongation, At Break, percent 2 in./min	D638-72 Type IV Specimen	450
Vicat Softening Temperature, °F	D1525-70	240
Brittleness Temperature, °F	D746-73	-180
Flexural Modulus, psi	D790-71	100,000

\*Based on parts molded @ 650F for 13 min

Table 5-2. Drop Impact of a Molded Container\*

Weight When Filled with Water	Temperature of Water	Drop Distance
Test 1. 800 gm	73°F	30 ft
Test 2. 800 gm	-20°F	30 ft

\*Based on 2-gal container molded @ 600°F for 14 min

This process of tank production requires less energy than that used to produce metal tanks; fabrication is thus less expensive. Due to time constraints, molds were made from fabricated and welded steel instead of cast aluminum. Cast aluminum molds, however, offer distinct advantages. First, using such molds produces greater radius corners and better fillets: these features strengthen the walls of the plastic tank, reducing the possibility of distortion. In addition, use of a cast tool allows shot-peening of the mold interior: such an interior produces a textured surface on the tanks eliminating the high gloss finish seen on the prototypes. The product finish thus more closely matches the standard military satin forest green finish.

Finally, the tanks were treated to reduce fuel permeation. Two methods are normally used: external epoxy coating and internal sulfonation. The external coating method was adopted, for Hollowform is neither licensed nor equipped to sulfonate. Therefore, after flame-treating the exteriors of the tanks, they were sprayed with Barafene No. 1003 (Inmount Corp) and oven-cured.

### 5.5. Testing

5.5.1. General. The results of the following tests demonstrate the superiority of the plastic tank in impact resistance, heat resistance, and fuel retention. Wyle Laboratories technicians assisted us in pressure and temperature tests.

5.5.2. Impact Drop Test. As a specified test requirement, a tank 3/4-full of water was dropped 20 feet onto concrete, with impact point at a 45-degree angle to axis. The test temperature was 70°F. After dropping a tank 25 ft, the tank was pressured to 4 psig and checked for leakage using a soap solution. No evidence of leakage appeared.

5.5.3. Falling Dart Test. The requirement was to strike a sample with a 1/4-in.-radius dart of 6 lbs; distance and material temperature were not specified. Hollowform's standard test method was thus used: with sample material at -20°F, it was struck with a 1/2-in.-radius dart. Having withstood 66 ft-lbs of pressure without visible fracture, the sample passed the test.

5.5.4. High Temperature Test. Wyle Laboratories made the following report: The plastic fuel tanks were "placed on 3 in./sic/ x 4 in./sic/ rails in the chamber and filled to their filler necks with customer-supplied diesel fuel. The fuel tanks were then subjected to the seven-day exposure at 130°F.

The fuel tanks completed the seven-day exposure with no signs of leakage or capillary weeping around any insert filling."<sup>1</sup> (See pp. 14 through 19 in Addendum for complete report.)

5.5.5. Leakage Test. All finished tanks were tested at 4 psig and found to be acceptable. (See ADDENDUM.)

ADDENDUM

**WYLE LABORATORIES**

12 April 1979

Hollowform, Inc.  
6345 Variel Avenue  
Woodland Hills, CA 91364

**ATTENTION:** Mr. Roy Newton  
**TEST TITLE:** High Temperature  
**REFERENCES:** Your Purchase Order No. 02153  
Wyle Laboratories Job No. 55404  
Government Contract No. DAAK30-78-C-0122

Gentlemen:

This is to certify that the enclosed Test Data Sheets contain true and correct data obtained in the performance of the test program as set forth in your purchase order.

Where applicable, instrumentation used in obtaining this data has been calibrated using standards which are traceable to the National Bureau of Standards.

**Test Results:**


Two Plastic Fuel Tanks, one each of Part Numbers RLSK-5701 and 19207-11669354, were submitted for a 7 day Temperature Test at +130°F. The Fuel Tanks were placed on 2" x 4" rails in the chamber and filled to their filler necks with customer supplied diesel fuel. The Fuel Tanks were then subjected to the 7 day exposure at +130°F. The Fuel Tanks completed the 7 day exposure with no signs of leakage or capillary weeping around any insert fittings. The test conditions attained are presented in the enclosed Data Sheet which includes a typical 24 hour temperature recording and the test equipment used. At the conclusion of the test, the Fuel Tanks were returned to Hollowform while still filled with diesel fuel.

Enclosures: Data Sheets ( 3 Pages)

STATE OF CALIFORNIA } ss.  
COUNTY OF LOS ANGELES }

C. D. Yiakas, Department Manager, being duly sworn, deposes and says: That the information contained in this report is the result of complete and carefully conducted tests and is to the best of his knowledge true and correct in all respects.

SUBSCRIBED and sworn to before me this 18 day of April, 19 79



W-781

17  
A-21

DEPARTMENT Mechanical SystemsTEST ENGINEER R. L. Rice  
R. L. Rice

TEST WITNESS \_\_\_\_\_

Not Applicable  
DCAS-QAR VERIFICATION

QUALITY CONTROL V. W. [Signature]

HOLLOWFORM, INC.  
6345 VARIEL AVE.  
WOODLAND HILLS, CALIF. 91364

PART TITLE: 5 Ton Army Tank  
PART NUMBER: 19207-11669354  
CONTRACT NUMBER: DAAK30-78-C-0122

HYDROSTATIC PRESSURE TEST  
=====

Serial No.	P.S.I.G.	Time Pressured	Results	Test Date	Performed By
<u>9-080-01</u>	<u>4</u>	<u>2min.</u>	<u>H2OK</u>	<u>11 April 79</u>	<u>LWB/DMC</u>
<u>9-080-02</u>	<u>4</u>	<u>2min.</u>	<u>H2OK</u>	<u>"</u>	<u>"</u>
<u>9-079-02</u>	<u>4</u>	<u>2min.</u>	<u>H2OK</u>	<u>"</u>	<u>"</u>
<u>9-079-01</u>	<u>4</u>	<u>2min.</u>	<u>H2OK</u>	<u>"</u>	<u>"</u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>
<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>	<u>          </u>

Weight of completed part: 36.5 pounds

Testing Witnessed by: Dorothy M<sup>C</sup>Clendon  
U.S. Army Rep.  
Warren, Michigan

*LWB*

PART TITLE: 5 Ton Army Tank  
PART NUMBER: 19207-11669354  
CONTRACT NUMBER: DAAK30-78-C-0122

[illegible][illegible]









19  
A-23

SwB

PART TITLE: 2½ Ton Army Tank  
PART NUMBER: RCK5701  
CONTRACT NUMBER: DAAK30-78-C-0122

JWB





1-1	COVER PLATE & GASKET	1-1	COVER PLATE & GASKET
1-2	TRIM FITTING	1-2	TRIM FITTING
1-3	ANCHOR BOLTING	1-3	ANCHOR BOLTING
1-4	END FITTING ONLY	1-4	END FITTING ONLY
1-5	GASKET	1-5	GASKET
1-6	FLANGE COLLAR	1-6	FLANGE COLLAR
1-7	SCREW	1-7	SCREW
1-8	FLANGING RING OF 1/2" DIA. 1/4" THICK	1-8	FLANGING RING OF 1/2" DIA. 1/4" THICK
1-9	FEED TUBE	1-9	FEED TUBE
1-10	GASKET	1-10	GASKET
1-11	GASKET	1-11	GASKET
1-12	ANCHORING JOINT OF 1/2" DIA.	1-12	ANCHORING JOINT OF 1/2" DIA.
1-13	FLAT PLATE	1-13	FLAT PLATE
1-14	GASKET	1-14	GASKET
1-15	FITTING ONLY	1-15	FITTING ONLY
1-16	ANCHOR	1-16	ANCHOR
1-17	ANCHOR	1-17	ANCHOR
1-18	ANCHOR	1-18	ANCHOR
1-19	ANCHOR	1-19	ANCHOR
1-20	ANCHOR	1-20	ANCHOR
1-21	ANCHOR	1-21	ANCHOR
1-22	ANCHOR	1-22	ANCHOR
1-23	ANCHOR	1-23	ANCHOR
1-24	ANCHOR	1-24	ANCHOR
1-25	ANCHOR	1-25	ANCHOR
1-26	ANCHOR	1-26	ANCHOR
1-27	ANCHOR	1-27	ANCHOR
1-28	ANCHOR	1-28	ANCHOR
1-29	ANCHOR	1-29	ANCHOR
1-30	ANCHOR	1-30	ANCHOR
1-31	ANCHOR	1-31	ANCHOR
1-32	ANCHOR	1-32	ANCHOR
1-33	ANCHOR	1-33	ANCHOR
1-34	ANCHOR	1-34	ANCHOR
1-35	ANCHOR	1-35	ANCHOR
1-36	ANCHOR	1-36	ANCHOR
1-37	ANCHOR	1-37	ANCHOR
1-38	ANCHOR	1-38	ANCHOR
1-39	ANCHOR	1-39	ANCHOR
1-40	ANCHOR	1-40	ANCHOR
1-41	ANCHOR	1-41	ANCHOR
1-42	ANCHOR	1-42	ANCHOR
1-43	ANCHOR	1-43	ANCHOR
1-44	ANCHOR	1-44	ANCHOR
1-45	ANCHOR	1-45	ANCHOR
1-46	ANCHOR	1-46	ANCHOR
1-47	ANCHOR	1-47	ANCHOR
1-48	ANCHOR	1-48	ANCHOR
1-49	ANCHOR	1-49	ANCHOR
1-50	ANCHOR	1-50	ANCHOR
1-51	ANCHOR	1-51	ANCHOR
1-52	ANCHOR	1-52	ANCHOR
1-53	ANCHOR	1-53	ANCHOR
1-54	ANCHOR	1-54	ANCHOR
1-55	ANCHOR	1-55	ANCHOR
1-56	ANCHOR	1-56	ANCHOR
1-57	ANCHOR	1-57	ANCHOR
1-58	ANCHOR	1-58	ANCHOR
1-59	ANCHOR	1-59	ANCHOR
1-60	ANCHOR	1-60	ANCHOR
1-61	ANCHOR	1-61	ANCHOR
1-62	ANCHOR	1-62	ANCHOR
1-63	ANCHOR	1-63	ANCHOR
1-64	ANCHOR	1-64	ANCHOR
1-65	ANCHOR	1-65	ANCHOR
1-66	ANCHOR	1-66	ANCHOR
1-67	ANCHOR	1-67	ANCHOR
1-68	ANCHOR	1-68	ANCHOR
1-69	ANCHOR	1-69	ANCHOR
1-70	ANCHOR	1-70	ANCHOR
1-71	ANCHOR	1-71	ANCHOR
1-72	ANCHOR	1-72	ANCHOR
1-73	ANCHOR	1-73	ANCHOR
1-74	ANCHOR	1-74	ANCHOR
1-75	ANCHOR	1-75	ANCHOR
1-76	ANCHOR	1-76	ANCHOR
1-77	ANCHOR	1-77	ANCHOR
1-78	ANCHOR	1-78	ANCHOR
1-79	ANCHOR	1-79	ANCHOR
1-80	ANCHOR	1-80	ANCHOR
1-81	ANCHOR	1-81	ANCHOR
1-82	ANCHOR	1-82	ANCHOR
1-83	ANCHOR	1-83	ANCHOR
1-84	ANCHOR	1-84	ANCHOR
1-85	ANCHOR	1-85	ANCHOR
1-86	ANCHOR	1-86	ANCHOR
1-87	ANCHOR	1-87	ANCHOR
1-88	ANCHOR	1-88	ANCHOR
1-89	ANCHOR	1-89	ANCHOR
1-90	ANCHOR	1-90	ANCHOR
1-91	ANCHOR	1-91	ANCHOR
1-92	ANCHOR	1-92	ANCHOR
1-93	ANCHOR	1-93	ANCHOR
1-94	ANCHOR	1-94	ANCHOR
1-95	ANCHOR	1-95	ANCHOR
1-96	ANCHOR	1-96	ANCHOR
1-97	ANCHOR	1-97	ANCHOR
1-98	ANCHOR	1-98	ANCHOR
1-99	ANCHOR	1-99	ANCHOR
1-100	ANCHOR	1-100	ANCHOR

# LIST OF REFERENCES

- <sup>1</sup> Yiakas, C. D. Data Sheet Report No. 55404, 12 April 1975, Wyle Laboratories, 128 Maryland St., El Segundo, CA, 90245

THIS PAGE LEFT BLANK INTENTIONALLY

APPENDIX B

GUIDELINES FOR

WRITING TECHNICAL DEFINITIONS

THIS PAGE LEFT BLANK INTENTIONALLY

## 1.0. DEFINING THROUGH SIMPLE CLASSIFICATION AND DIFFERENTIATION AND THROUGH ETYMOLOGY

The writer should begin by stating the word to be defined (Holography is \_\_\_\_\_), classifying it, and then differentiating it from other items in the same class. If it is an unusual word, he also may want to give its etymology, that is, to provide information about the literal meanings of its parts [prefix(es), root(s), and suffix(es)]. He might, for example, consider this definition of chromatography (the quoted material is from Webster's Ninth New Collegiate Dictionary): Chromatography, which literally means color writing, is "the separation of closely related compounds by allowing their passage through an absorbent material so that each is absorbed in a different colored layer." Or he might study the definition of isothermal compression offered by the authors of Modern Technical Writing: Isothermal compression is the compression of a gas under such conditions that the heat generated by compression is removed as fast as it is generated, so that the temperature of the gas does not change. The meaning may be seen in that iso is a combining form meaning equal and that thermal refers to heat. Avoid "is when" or "is where" structures after the term.

## 2.0. DEFINING BY SUBDIVIDING

If the word can be broken into several major classes or subdivisions, the writer should designate these classes and distinguish among them. For example, he might write the following: "There are essentially two methods of molding cross-linked polyethylene--blow-molding and rotational-molding. Blow-molding is \_\_\_\_\_. Rotational-molding is \_\_\_\_\_."

## 3.0. DEFINING THROUGH EXAMPLES

If possible, a writer should give three or four examples of applications or products of a process. He should try to use examples that a reader might be familiar with.

## 4.0. DEFINING THROUGH RELATED TERMS

If the term can be easily confused with another term (either of broader or more specific meaning), the writer should distinguish between the terms.

## 5.0. DEFINING A PROCESS

If the writer is defining a process rather than giving a technical description of a process, he will want to indicate, as the authors of Modern Technical Writing suggest, "why, where, when, and by whom the process is performed" as well as what special instruments or skills are needed for its effective performance. Often a technical definition precedes the more detailed technical description of an object or process.

## 6.0. DEFINING AN OBJECT

If a writer is defining an object, he might want to indicate its purpose, its main parts, its distinguishing attributes, and its uses. He could also include information about its origin, i.e., its invention or discovery. Appropriate figures--be they photographs, diagrams, or drawings--are also helpful as supplements to the text.

APPENDIX C

GUIDELINES FOR WRITING  
TECHNICAL DESCRIPTIONS OF OBJECTS

THIS PAGE LEFT BLANK INTENTIONALLY

## 1.0. DEFINITION IN DESCRIPTION

A technical description frequently begins with a simple definition of the object to be described in detail. The simple definition not only classifies and differentiates, but it also explains the overall physical features of the object--its size, shape, weight, composition, etc.

## 2.0. ORGANIZATION OF DESCRIPTION

### 2.1. General.

The organization of the description is based on a listing of parts; however, the order in which the parts are discussed can vary. One of the following methods of organization can be used or they can be used in combination.

### 2.2. Organization Based on Visual Survey.

The organization of a description is occasionally based on visual survey, that is, in the manner in which one looks at the parts of an object. Generally, these principles of visual perception apply: objects which are primarily horizontal in design are viewed from left to right while objects which are primarily of vertical design are viewed from top to bottom. One might also visually survey an object in a clockwise fashion or one might first survey the exterior and then survey all or part of the interior. As one seeks to show relationships among parts, one should use directional phrases such as to the right, directly below, and in the upper right hand corner. Further, as a general rule, once one establishes a direction of movement, he should hold to it. Finally, in describing individual parts, it is helpful to provide any details of size, shape, composition, etc., which will help the reader visualize the object. For example, one might use letters to describe shape as in L-shaped, S-shaped, etc. For the most part, simple objects can be surveyed by a single-directional visual survey; more complex equipment may involve a change in directional movement or a combination of several separate moves. As a general rule however, visual survey should never move from right to left, from bottom to top, in a counterclockwise fashion, or from detail to overview.

### 2.3. Organization Based on the Order in Which the Parts Perform Their Functions.

The organization of technical description is most frequently based on the order in which the parts perform their functions. This method is, of course, most appropriate when functions occur in sequence. If several parts function simultaneously to produce a single result in a single system, the writer should seek to clarify their relationship. If they function simultaneously as parts of different systems, he will only confuse the reader by noting their simultaneous movement. The governing principle here is logical sequence and interrelationship.

DISTRIBUTION LIST

	Copies
Commander US Army Tank-Automotive Command ATTN: AMSTA-TSL Warren, MI 48090	2
Manager Defense Logistics Studies Information Exchange ATTN: DRXMC-D Fort Lee, VA 23801	2
Commander Defense Technical Information Center Bldg. 5, Cameron Station ATTN: DDAC Alexandria, VA 22314	12